

产品系列数据表

HPL (> 130 V)



应用领域


- 舞台及剧场
- 演播室，电视电影
- 建筑照明及灯光秀

产品特点


- Ultra compact filament design (UCF) for high lumen output
- Unique gas fill which improves light output and minimizes risk of arc-out
- Special heat sink base for maximum durability in high temperature applications
- Reinforced pinch seal for extra mechanical strength
- Foam packaging for easier handling and installation
- Optimum system performance with TP22H socket



产品系列数据表



HPL 575W



HPL 750W

产品系列数据表

技术参数

| | 电参数 | | Physical Attributes & Dimensions | 寿命 |
|--------------------------|-------|-------|----------------------------------|--------------------|
| 产品描述 | 标称功率 | 标称电压 | 灯头 (标准名称) | Average Rated Life |
| HPL 93728 575 W 230 V | 575 W | 230 V | G9.5 w/Hsink | 400 hr |
| HPL 93728 LL 575 W 230 V | 575 W | 230 V | G9.5 w/Hsink | 1500 hr |
| HPL 93728 575 W 240 V | 575 W | 240 V | G9.5 w/Hsink | 400 hr |
| HPL 93728 LL 575 W 240 V | 575 W | 240 V | G9.5 w/Hsink | 1500 hr |
| HPL 93729 750 W 230 V | 750 W | 230 V | G9.5 w/Hsink | 300 hr |
| HPL 93729 LL 750 W 230 V | 750 W | 230 V | G9.5 w/Hsink | 1500 hr |
| HPL 93729 750 W 240 V | 750 W | 240 V | G9.5 w/Hsink | 300 hr |
| HPL 93729 LL 750 W 240 V | 750 W | 240 V | G9.5 w/Hsink | 1500 hr |

产品系列数据表

安全建议

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (cover panel etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. Because of the heat produced only heat-resistant lamp connections (holders) may be used. Do not operate near people, or any materials that are flammable, sensitive to heat or affected by drying out. Detailed information is available on request.

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。