

XBO 3000 W/DTP OFR

XBO for CHRISTIE Projectors


Areas of application

- Digital Cinema Projection



Product features and benefits

- High luminance for brighter screen illumination
- A lifetime of consistent performances with constant 6000 K color temperature
- Continuous spectrum in the visible range
- High arc stability
- High arc stability
- Dimmable over a wide range
- Hot restart



Product datasheet

Technical data

General Product Information

Product number (Americas)	69154
Product name (Americas)	XBO 3000W/DTP 1/CS 1/SKU
Global order reference	XBO 3000 W/DTP OFR


Electrical Data

Nominal wattage	3000 W
Nominal voltage	31 V
Nominal current	101 A
Current control range	74...109 A
Type of current	DC

Photometric Data

Nominal luminous flux	130000 lm
Light center length (LCL)	160.0 mm

Physical Attributes & Dimensions



Electrode gap (cold)	6.0 mm
Base (anode)	SFa30-14
Base (cathode)	SFc30-14
Diameter	60.0 mm
Diameter (in)	2.362 in
Diameter	60.0 mm
Length	397.0 mm
Length with base excl. base pins/connection	354.00 mm
Product weight	536.00 g

Product datasheet

Operating Conditions

Burning position	s15/p15 ¹⁾
Cooling	Forced
Max. permitted ambient temp. pinch point	230 °C

¹⁾ For vertical burning position: anode (+) on top

Lifetime Data

Nominal lifetime	1500 hr
Warranty hours	1500 hrs
Service warranty lifetime	2500 hr

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4008321191540 4052899509474
Declaration no. in SCIP database	cdf74e98-4a09-4bdf-8cd1-2fd9bd8791fb
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.

Product datasheet

Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899509474	XBO 3000 W/DTP OFR	Shipping carton box 1	590 mm x 234 mm x 234 mm	32.31 dm ³	1669.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
