

## XBO 2300 W/DTS OFR

XBO for CHRISTIE Projectors



### Areas of application

- Digital Cinema Projection

### Product features and benefits

- High luminance for brighter screen illumination
- A lifetime of consistent performances with constant 6000 K color temperature
- Continuous spectrum in the visible range
- High arc stability
- High arc stability
- Dimmable over a wide range
- Hot restart



# Product datasheet

## Technical data

### General Product Information

Product number (Americas)	68889
Product name (Americas)	XBO 2300W/DTS 1/CS 1/SKU
Global order reference	XBO 2300 W/DTS OFR


### Electrical Data

Nominal wattage	2300 W
Nominal voltage	27 V
Nominal current	84 A
Current control range	60...90 A
Type of current	DC

### Photometric Data

Light center length (LCL)	100.5 mm
---------------------------	----------

### Physical Attributes & Dimensions



Electrode gap (cold)	3.7 mm
Base (anode)	Cable
Base (cathode)	SFc30-20
Diameter	46.0 mm
Diameter	46.0 mm
Length	245.0 mm
Length with base excl. base pins/connection	202.00 mm
Connector: presence	Yes
Product weight	370.00 g

### Operating Conditions

## Product datasheet

<b>Burning position</b>	s15/p15 <sup>1)</sup>
<b>Cooling</b>	Forced
<b>Max. permitted ambient temp. pinch point</b>	230 °C

<sup>1)</sup> For vertical burning position: anode (+) on top

### Lifetime Data

<b>Nominal lifetime</b>	1000 hr
<b>Warranty hours</b>	1000 hrs
<b>Service warranty lifetime</b>	1200 hr

### Environmental & Regulatory Information

<b>Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)</b>	
<b>Primary article identifier</b>	4052899359659
<b>Declaration no. in SCIP database</b>	bccb6f98-b1df-4b09-9777-7d0c95b57df6
<b>Candidate list substance 1</b>	Lead
<b>CAS No. of substance 1</b>	7439-92-1
<b>Safe use instruction</b>	The identification of the Candidate List substance is sufficient to allow safe use of the article.

## Product datasheet

---

### Safety advice

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899359659	XBO 2300 W/DTS OFR	Shipping carton box 1	500 mm x 204 mm x 204 mm	20.81 dm <sup>3</sup>	1166.00 g

---

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

---