

XBO for SONY Projectors


Användningsområde

- Digital Cinema Projection



Produktegenskaper

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K - simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart



Datablad produktfamilj

Tekniska data

Produktbeskrivning	Elektriska data		Livslängder	
	Nominell watttal	Strömstyrningsområde	Warranty hours	Service Warranty Lifetime
XBO 2000 W/HPS L OFR	2000 W	46...87 A	3000 hrs	3500 hr
XBO 3000 W/HPS OFR	3000 W	60...112 A	1000 hrs	1300 hr
XBO 4200 W/HPS OFR	4200 W	73...137 A	700 hrs	850 hr
XBO 4200 W/HPS LL	4200 W	69...131 A	1000 hrs	1200 hr

Datablad produktfamilj

Säkerhetsanvisningar

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

Appliktionsråd

För mer detaljerad applikationsinformation och grafik, vänligen se produktdatablad

Friskrivningsklausul

Kan ändras utan föregående notifiering. Felaktigheter och försummelse undantagna. Se alltid till att använda den senaste utgåvan.