

HBO R & HXP R ≤ 200W with Reflector



应用领域


- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Microscopy
- Solar Simulation

产品特点

- High luminance / radiance with intense point source
- Broad spectral distribution in the visible and ultraviolet range
- Enhanced UV characteristics available on some types
- High arc stability



产品系列数据表



HBO R 103W

产品系列数据表

技术参数

产品描述	电参数			寿命
	标称功率	灯泡电压	灯泡电流	Average Rated Life
HBO R 103 W/45	103 W	20...25 V ²⁾	4.0...5.0 A	300 hr
HXP R 120 W/45 C VIS ¹⁾	120 W	60...90 V ³⁾	1.4 A	2000 hr
HXP R 120 W/45 C UV ¹⁾	120 W	60...90 V ³⁾	1.4 A	2000 hr
HXP R 200 W/45 M ¹⁾	200 W	60...96 V ³⁾	3.4 A	2000 hr

¹⁾ To be operated with OSRAM PT VIP EVG

²⁾ 初始电气值

³⁾ 初始电压范围

产品系列数据表

安全建议

Due to their high luminance, UV radiation, and high internal pressure in the hot state, HBO and HXP lamps may only be operated in enclosed lamp casings designed for their operation. Since mercury is released if the lamp breaks, special safety precautions must be taken. More information is available upon request, or can be found in the leaflet or operating instructions included with the lamp. You can also review our Product Safety Guide.

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。