

Halogen (< 75 V) Single End




应用领域


- Microscopy
- Laboratory & Analysis
- UV Curing
- Fiber Illumination
- Surgical & Dental Overhead

产品特点


- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable




产品系列数据表




HALOGEN NIEDERVOLT LAMPE PG 22




LOW-VOLTAGE HALOGEN LAMP 64250




LOW-VOLTAGE HALOGEN LAMP 62138



LOW-VOLTAGE HALOGEN LAMP 64611




LOW-VOLTAGE HALOGEN LAMP 64668




LOW-VOLTAGE HALOGEN LAMP 64640

产品系列数据表



LOW-VOLTAGE HALOGEN LAMP 64628



LOW-VOLTAGE HALOGEN LAMP 64643

产品系列数据表

技术参数

	General Product Information		电参数	Physical Attributes & Dimensions
产品描述	ANSI编码	LIF	标称电压	灯头 (标准名称)
64222 10 W 6 V	-	-	6 V	PG22
64223 10 W 6 V	-	M/43	6 V	G4
64225 10 W 6 V	ESA/FHS	M/29	6 V	G4
64250 HLX	ESB	M/33	6 V	G4
64251 HLX	-	-	6 V	PG22
64265 HLX	-	-	6 V	G4
64260 30 W 12 V	-	M/185	12 V	PG22
64275 AX	-	M/137	6 V	G4
64258 20 W 12 V	-	-	12 V	G4
64602 50 W 12 V	-	M/134	12 V	G6.35
64610 HLX	BRL	A1/220	12 V	G6.35
64611 HLX	-	-	12 V	G6.35
64604 50 W 12 V	-	-	12 V	GY6.35
64668 XIR	-	-	22.8 V	G6.35
64621 HLX	-	-	12 V	PG22
64623 HLX	EVA	M/28	12 V	GY6.35
64638 HLX	-	-	24 V	G6.35
64625 HLX	FCR	A1/215	12 V	GY6.35
64628 100 W 12 V	FDT	A1/261	12 V	GY9.5
62138 HLX	-	-	12 V	G6.35
64626 HLX ¹⁾	EHE	A1/45	12 V	PG22
64647 120 W 24 V	-	-	22.8 V	G6.35
64650 50 W 22,8 V	-	-	22.8 V	G6.35
64633 HLX	BRJ	A1/234	15 V	G6.35
64640 HLX	FCS	A1/216	24 V	G6.35
64292 XIR	-	-	22.8 V	G6.35
64642 HLX	FDV	M/184	24 V	G6.35
64641 HLX	-	-	24 V	G6.35
64643 150 W 24 V	FDS	A1/262	24 V	GY9.5
64654 HLX ¹⁾	-	-	24 V	GY9.5
64655 HLX	EHJ	A1/223	24 V	G6.35
64656 HLX	FNT	-	24 V	G6.35
64657 HLX	EVC	M/33	24 V	G6.35
64663 HLX	EVD	A1/239	36 V	G6.35
64664 HLX	-	A1/270	36 V	G6.35
64665 HLX	-	A1/166	36 V	G6.35

	寿命
产品描述	Average Rated Life
64222 10 W 6 V	300 hr
64223 10 W 6 V	300 hr

产品系列数据表

	寿命
产品描述	Average Rated Life
64225 10 W 6 V	100 hr
64250 HLX	100 hr
64251 HLX	100 hr
64265 HLX	100 hr
64260 30 W 12 V	50 hr
64275 AX	25 hr
64258 20 W 12 V	2000 hr
64602 50 W 12 V	1100 hr
64610 HLX	50 hr
64611 HLX	100 hr
64604 50 W 12 V	2000 hr
64668 XIR	350 hr
64621 HLX	2000 hr
64623 HLX	1500 hr
64638 HLX	300 hr
64625 HLX	50 hr
64628 100 W 12 V	50 hr
62138 HLX	50 hr
64626 HLX ¹⁾	50 hr
64647 120 W 24 V	1000 hr
64650 50 W 22,8 V	1000 hr
64633 HLX	50 hr
64640 HLX	50 hr
64292 XIR	600 hr
64642 HLX	300 hr
64641 HLX	200 hr
64643 150 W 24 V	100 hr
64654 HLX ¹⁾	300 hr
64655 HLX	50 hr
64656 HLX	75 hr
64657 HLX	300 hr
64663 HLX	50 hr
64664 HLX	150 hr
64665 HLX	300 hr

¹⁾ 定制生产

产品系列数据表

安全建议

为避免人身伤害或财产损失，卤素灯只能在设计有合适结构（护罩、网格等）的合适灯具中操作，以确保在灯破裂时无零件/碎片崩出。还必须给出警告标志来指示这些灯会散发高热量。详细资讯可根据要求索要。

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。