

# XENARC ULTRA LIFE

Superior life and 10 year guarantee



**10 year OSRAM guarantee**

For a worry-free driving pleasure. Refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions



**Extra lifetime**

Up to four times longer lifetime compared to standard xenon lamps



**More durability**

For longer replacement cycles and additional reliability and comfort



**The durable light with up to four times longer lifetime**

XENARC ULTRA LIFE xenon lamps were developed with durability in mind. These long-life headlight lamps make life just that little bit more hassle-free, thanks to a lifetime up to four times longer compared to standard xenon lamps. Besides, these reliable lights impress with a service life up to 300,000 km (with an average annual mileage of 14,259 km and 60% light on)! For XENARC ULTRA LIFE lamps, OSRAM provides a unique 10 year guarantee for end consumers ([www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)). Thus, you not only save money on costly replacements, but also save yourself future stress and downtime. Please note: XENARC lamp change is recommended to be carried out by a professional.

## Product family datasheet

### Technical data

| Product description                 | Electrical data |                 |                 |              | Photometrical data |                         | Dimensions & weight |
|-------------------------------------|-----------------|-----------------|-----------------|--------------|--------------------|-------------------------|---------------------|
|                                     | Power input     | Nominal voltage | Nominal wattage | Test voltage | Luminous flux      | Luminous flux tolerance | Diameter            |
| XENARC ULTRA LIFE D1S <sup>1)</sup> | 35 W            | 85.0 V          | 35.00 W         | 13.5 V       | 3200 lm            | ±15 %                   | 9 mm                |
| XENARC ULTRA LIFE D2S <sup>1)</sup> | 35 W            | 85.0 V          | 35.00 W         | 13.5 V       | 3200 lm            | ±15 %                   | 9 mm                |
| XENARC ULTRA LIFE D3S <sup>1)</sup> | 35 W            | 42.0 V          | 35.00 W         | 13.5 V       | 3200 lm            | ±15 %                   | 9 mm                |
| XENARC ULTRA LIFE D4S <sup>1)</sup> | 35 W            | 42.0 V          | 35.00 W         | 13.5 V       | 3200 lm            | ±15 %                   | 9 mm                |

| Product description                 | Capabilities | Certificates & standards | Environmental information<br>Information according Art. 33 of EU<br>Regulation (EC) 1907/2006 (REACH) |  |
|-------------------------------------|--------------|--------------------------|---|--|
|                                     | Technology   | ECE category             | Date of Declaration   | Primary Article Identifier   |
| XENARC ULTRA LIFE D1S <sup>1)</sup> | HID          | D1S <sup>2)</sup>        | 30-12-2022  | 4052899425514  <br>4052899429598  <br>4052899429611                    |
| XENARC ULTRA LIFE D2S <sup>1)</sup> | HID          | D2S <sup>2)</sup>        | 25-11-2022  | 4052899425576  <br>4052899429659  <br>4052899429673                    |
| XENARC ULTRA LIFE D3S <sup>1)</sup> | HID          | D3S <sup>2)</sup>        | 13-01-2023  | 4052899425606  <br>4052899429710  <br>4052899429734  <br>4052899429758 |
| XENARC ULTRA LIFE D4S <sup>1)</sup> | HID          | D4S <sup>2)</sup>        | 11-10-2022  | 4052899425637  <br>4052899429772  <br>4052899429819  <br>4052899429796 |

| Product description                 | Candidate List Substance 1 | CAS No. of substance 1 | Safe Use Instruction   | Declaration No. in SCIP database  |
|-------------------------------------|----------------------------|------------------------|--|---|
| XENARC ULTRA LIFE D1S <sup>1)</sup> | Leadlead                   | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. | e59d8923-da88-412b-879a-a321dc37e951   dbae34d6-0162-4aca-9ca3-4b6e003e5fba |
| XENARC ULTRA LIFE D2S <sup>1)</sup> | Lead                       | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. | ac5968cd-c357-48e1-9a75-7023de759a2e   0e906b5d-b5f0-4059-88bb-8de1f85d5ed2 |
| XENARC ULTRA LIFE D3S <sup>1)</sup> | leadLead                   | 7439-92-1              | The identification of the Candidate List substance is sufficient to allow safe use of the article. | a4977431-0469-4938-bbae-2f7fbc300030   4dac5460-9f2d-4974-8f46-2378b4246f3e |

## Product family datasheet






| Product description                 | Candidate List Substance 1         | CAS No. of substance 1 | Safe Use Instruction | Declaration No. in SCIP database |
|-------------------------------------|------------------------------------|------------------------|----------------------|----------------------------------|
| XENARC ULTRA LIFE D4S <sup>1)</sup> | No declarable substances contained |                        |                      | In work                          |

<sup>1)</sup> Reduced UV emission/For projection headlights/ECE approval and DOT label

<sup>2)</sup> To be operated only with approved electronic control gear

## Product family datasheet

### Download Data

| File  |  |
|---|--|
|  | Brochures<br>724901_ULTRA LIFE Leaflet EN          |
|  | 360 Degree Image<br>XENARC ULTRA LIFE D1S 66140ULT |
|  | 360 Degree Image<br>XENARC ULTRA LIFE D2S 66240ULT |
|  | 360 Degree Image<br>XENARC ULTRA LIFE D3S 66340ULT |
|  | 360 Degree Image<br>XENARC ULTRA LIFE D4S 66440ULT |

#### Safety advice

XENARC lamp change is recommended to be carried out by a professional.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

