
XENARC ULTRA LIFE

Xenon headlight lamps



Areas of application

- Headlight

Product family datasheet

Technical data

Product description	Electrical data				Photometrical data		Dimensions & weight	Additional product data
	Power input	Nominal voltage	Nominal wattage	Test voltage	Luminous flux	Luminous flux tolerance	Diameter	Base (standard designation)
XEN ULT 66140ULT ¹⁾	35 W	85.0 V	35.00 W	13.5 V	3200 lm	±15 %	9 mm	PK32d-2
XEN ULT 66240ULT ¹⁾	35 W	85.0 V	35.00 W	13.5 V	3200 lm	±15 %	9 mm	P32d-2
XEN ULT 66340ULT ¹⁾	35 W	42.0 V	35.00 W	13.5 V	3200 lm	±15 %	9 mm	PK32d-5
XEN ULT 66440ULT ¹⁾	35 W	42.0 V	35.00 W	13.5 V	3200 lm	±15 %	9 mm	P32d-5

Product description	Certificates & standards
	ECE category
XEN ULT 66140ULT ¹⁾	D1S ²⁾
XEN ULT 66240ULT ¹⁾	D2S ²⁾
XEN ULT 66340ULT ¹⁾	D3S ²⁾
XEN ULT 66440ULT ¹⁾	D4S ²⁾

¹⁾ Reduced UV emission/For projection headlights/ECE approval and DOT label

²⁾ To be operated only with approved electronic control gear

Product family datasheet

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.