

## XEN ULT 66340ULT

XENARC ULTRA LIFE | Xenon headlight lamps



### Areas of application

- Headlight

## Product datasheet

### Technical data


#### Electrical data

Power input	35 W
Nominal voltage	42.0 V
Nominal wattage	35.00 W
Test voltage	13.5 V
Power input tolerance	±3 %

#### Photometrical data

Luminous flux	3200 lm
Luminous flux tolerance	±15 %
Color temperature	4150 K

#### Dimensions & weight



Diameter	9 mm
Product weight	63.00 g
Length	80.0 mm

#### Additional product data

Base (standard designation)	PK32d-5
-----------------------------	---------

#### Certificates & standards


ECE category	D3S <sup>1)</sup>
Approval marks – approval	E1 approval

<sup>1)</sup> To be operated only with approved electronic control gear

## Product datasheet

### Safety advice

XENARC lamp change is recommended to be carried out by a professional.



### Others graphics

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899425606	XEN ULT 66340ULT	Folding carton box 1	53 mm x 46 mm x 93 mm	0.23 dm <sup>3</sup>	82.96 g
4052899425613	XEN ULT 66340ULT	Shipping carton box 4	118 mm x 98 mm x 97 mm	1.12 dm <sup>3</sup>	364.05 g
4052899425620	XEN ULT 66340ULT	Shipping carton box 48	- x - x -		
4052899429710	XEN ULT 66340ULT	Hard Cover Box 2	114 mm x 48 mm x 106 mm	0.58 dm <sup>3</sup>	218.08 g
4052899429727	XEN ULT 66340ULT	Shipping carton box 10	257 mm x 129 mm x 121 mm	4.01 dm <sup>3</sup>	1170.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.