

## XENARC ULTRA LIFE D2S

Superior life and 10 year guarantee



### 10 year OSRAM guarantee

For a worry-free driving pleasure. Refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions



### Extra lifetime

Up to four times longer lifetime compared to standard xenon lamps



### More durability

For longer replacement cycles and additional reliability and comfort



### The durable light with up to four times longer lifetime

XENARC ULTRA LIFE xenon lamps were developed with durability in mind. These long-life headlight lamps make life just that little bit more hassle-free, thanks to a lifetime up to four times longer compared to standard xenon lamps. Besides, these reliable lights impress with a service life up to 300,000 km (with an average annual mileage of 14,259 km and 60% light on)! For XENARC ULTRA LIFE lamps, OSRAM provides a unique 10 year guarantee for end consumers ([www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)). Thus, you not only save money on costly replacements, but also save yourself future stress and downtime. Please note: XENARC lamp change is recommended to be carried out by a professional.

# Product datasheet

## Technical data


### Electrical Data

|                       |        |
|-----------------------|--------|
| Power input           | 35 W   |
| Nominal voltage       | 85 V   |
| Nominal wattage       | 35 W   |
| Power input tolerance | ±3 %   |
| Test voltage          | 13.5 V |

### Photometric Data

|                         |         |
|-------------------------|---------|
| Nominal luminous flux   | 3200 lm |
| Luminous flux tolerance | ±15 %   |
| Color temperature       | 4300 K  |

### Physical Attributes & Dimensions



|                |         |
|----------------|---------|
| Lamp base      | P32d-2  |
| Length         | 77.3 mm |
| Diameter       | 9 mm    |
| Product weight | 16.10 g |

### Lifetime Data

|           |          |
|-----------|----------|
| Guarantee | 10 years |
|-----------|----------|

### Capabilities

|            |     |
|------------|-----|
| Technology | HID |
|------------|-----|

### Certificates & standards


|                           |                   |
|---------------------------|-------------------|
| ECE category              | D2S <sup>1)</sup> |
| Approval marks – approval | E1 approval       |

## Product datasheet

1) To be operated only with approved electronic control gear

### Environmental & Regulatory Information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |  |
|---|--|
| Primary article identifier  | 4062172404242   4052899425576   4052899429659  |
| Candidate list substance 1  | Lead   |
| CAS No. of substance 1  | 7439-92-1  |
| Safe use instruction  | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration no. in SCIP database                                      | ac5968cd-c357-48e1-9a75-7023de759a2e   0e906b5d-b5f0-4059-88bb-8de1f85d5ed2                        |



ref\_pim\_amsproductinfographics




### Logistical Data

| Product code  | Product description   | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume               | Gross weight |
|---------------|-----------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4052899425576 | XENARC ULTRA LIFE D2S | Folding carton box 1         | 53 mm x 46 mm x 92 mm                | 0.61 dm <sup>3</sup> | 36.00 g      |
| 4052899425583 | XENARC ULTRA LIFE D2S | Shipping carton box 4        | 115 mm x 101 mm x 103 mm             | 1.20 dm <sup>3</sup> | 176.00 g     |
| 4062172404242 | XENARC ULTRA LIFE D2S | HFB ECO 2                    | 100 mm x 51 mm x 120 mm              | 0.61 dm <sup>3</sup> | 62.00 g      |
| 4062172404259 | XENARC ULTRA LIFE D2S | Shipping carton box 4        | 113 mm x 111 mm x 134 mm             | 1.68 dm <sup>3</sup> | 166.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Product datasheet

### Download Data

| File  |   |
|---|---|
|  | User instruction<br>GPRS_Safety symbols instructions                |
|  | Brochures<br>ULTRA LIFE Leaflet EN                                  |
|  | ref_pim_amsproduct360degreeimages<br>XENARC ULTRA LIFE D2S 66240ULT |

#### Safety advice

XENARC lamp change is recommended to be carried out by a professional.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



# OSRAM