

# XENARC ULTRA LIFE

Superior life and 10 year guarantee



### 10 year OSRAM guarantee

For a worry-free driving pleasure.  
Register online: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)



### Extra lifetime

Up to four times longer lifetime compared to standard xenon lamps



### More durability

For longer replacement cycles and additional reliability and comfort



### The durable light with up to four times longer lifetime

XENARC ULTRA LIFE xenon lamps were developed with durability in mind. These long-life headlight lamps make life just that little bit more hassle-free, thanks to a lifetime up to four times longer compared to standard xenon lamps. Besides, these reliable lights impress with a service life up to 300,000 km (with an average annual mileage of 14,259 km and 60% light on)! For XENARC ULTRA LIFE lamps, OSRAM provides a unique 10 year guarantee for end consumers with online registration ([www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)). Thus, you not only save money on costly replacements, but also save yourself future stress and downtime. Please note: XENARC lamp change is recommended to be carried out by a professional.

## Product family datasheet

### Technical data

Product description	Electrical data null					Photometrical data null	
	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage	Luminous flux	Luminous flux tolerance
XENARC ULTRA LIFE D1S <sup>1)</sup>	35 W	85.0 V	35.00 W	±3 %	13.5 V	3200 lm	±15 %
XENARC ULTRA LIFE D2S <sup>1)</sup>	35 W	85.0 V	35.00 W	±3 %	13.5 V	3200 lm	±15 %
XENARC ULTRA LIFE D3S <sup>1)</sup>	35 W	42.0 V	35.00 W	±3 %	13.5 V	3200 lm	±15 %
XENARC ULTRA LIFE D4S <sup>1)</sup>	35 W	42.0 V	35.00 W	±3 %	13.5 V	3200 lm	±15 %

Product description	Dimensions & weight null		Additional product data null	Capabilities null	Certificates & standards null	Environmental information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
	Length	Diameter	Base (standard designation)	Technology	ECE category	Date of Declaration
XENARC ULTRA LIFE D1S <sup>1)</sup>	83.2 mm	9 mm	PK32d-2	HID	D1S <sup>2)</sup>	19-01-2022
XENARC ULTRA LIFE D2S <sup>1)</sup>	77.3 mm	9 mm	P32d-2	HID	D2S <sup>2)</sup>	19-01-2022
XENARC ULTRA LIFE D3S <sup>1)</sup>	83.2 mm	9 mm	PK32d-5	HID	D3S <sup>2)</sup>	19-01-2022
XENARC ULTRA LIFE D4S <sup>1)</sup>	77.3 mm	9 mm	P32d-5	HID	D4S <sup>2)</sup>	19-01-2022






Product description	Primary Article Identifier	Declaration No. in SCIP database
XENARC ULTRA LIFE D1S <sup>1)</sup>	4052899425514   4052899429598   4052899429611	In work
XENARC ULTRA LIFE D2S <sup>1)</sup>	4052899425576   4052899429659	In work
XENARC ULTRA LIFE D3S <sup>1)</sup>	4052899425606   4052899429710   4052899429734   4052899429758	In work
XENARC ULTRA LIFE D4S <sup>1)</sup>	4052899425637   4052899429772   4052899429819   4052899429796	In work

<sup>1)</sup> Reduced UV emission/For projection headlights/ECE approval and DOT label

<sup>2)</sup> To be operated only with approved electronic control gear

## Product family datasheet

### Download Data

File	
	Brochures 724901_ULTRA LIFE Leaflet EN
	360 Degree Image XENARC ULTRA LIFE D1S 66140ULT
	360 Degree Image XENARC ULTRA LIFE D2S 66240ULT
	360 Degree Image XENARC ULTRA LIFE D3S 66340ULT
	360 Degree Image XENARC ULTRA LIFE D4S 66440ULT

#### Safety advice

XENARC lamp change is recommended to be carried out by a professional.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

