

LEDDriving BASIC P21/5W



Technical data

Product information

Order reference	1357CW
Product type (off-road vs. on-road)	Off-road ≙ P21/5W
Application (Category and Product specific)	Mainly used for signal/ indicator applications

Electrical data

Power input	1.44 W
Nominal voltage	120 V
Nominal wattage	120 W
Test voltage	13.5 V
Power input tolerance	±20 %

Photometrical data

Luminous flux	85/25 lm
Luminous flux tolerance	±20 %
Color temperature	6000 K
Light color LED	Cool white

Dimensions & weight

Diameter	2000 mm
Product weight	1324 g
Length	382 mm

Lifespan

Lifespan B3	2000 h
Lifespan Tc	2000 h
Guarantee	4 years

Product datasheet

Additional product data

Base (standard designation)	BAY15d
-----------------------------	--------

Capabilities

Technology	LED
------------	-----

Country specific categorizations

Order reference	1357CW
-----------------	--------

Environmental information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899414518 4052899414495 4052899427327 4052899463295 4052899463080
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	fe6d71fd-c80e-400d-8cc2-14ed29394294 1d480114-7d33-4144-80cc-0d5f7210d25e e9e1666a-1f1f-4c57-897e-b5d1a43415ca 71710aae-de5e-4bc7-9841-c54466748320 9bf3b981-7442-439c-a86d-e513fc794734

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899463295	LEDiving BASIC \triangleq P21/5W	Blister 2	- x - x -		
4052899463301	LEDiving BASIC \triangleq P21/5W	Shipping carton box 20	280 mm x 80 mm x 103 mm	2.31 dm ³	370.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	Brochures LEDiving Retrofits - Exchange overview (EN)

Product datasheet

Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.