

LEDiving BASIC T4W



Product family datasheet

Technical data

Product description	Product information			Electrical data		
	Order reference	Product type (off-road vs. on-road)	Application (Category and Product specific)	Power input	Nominal voltage	Nominal wattage
LEDDriving BASIC \triangleq T4W	3750CW	Off-road \triangleq T4W	Mainly used for signal/ indicator/ interior applications	0.78 W	12.0 V	0.65 W

Product description	Test voltage	Photometrical data		Dimensions & weight	Lifespan		Capabilities
		Luminous flux	Luminous flux tolerance	Diameter	Lifespan B3	Lifespan Tc	Technology
LEDDriving BASIC \triangleq T4W	13.5 V	30 lm	± 20 %	9.5 mm	2000 h	2000 h	LED

Product description	Environmental information			
	Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)			
Product description	Date of Declaration	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1
LEDDriving BASIC \triangleq T4W	06-03-2024	4052899414655 4052899414617 4052899427471 4052899463066 4052899463271	Lead	7439-92-1

Product description	Safe Use Instruction	Declaration No. in SCIP database
LEDDriving BASIC \triangleq T4W	The identification of the Candidate List substance is sufficient to allow safe use of the article.	dc70588f-5433-4c78-9a81-18450deb8f7c 9add2d47-cd43-47d0-90e8-b42553d559f6 a1bf53bb-4f21-4d5b-a18e-23d37d00db14 aadf4566-2f5c-420c-940e-ab52c14c2128 4ed996ff-d5b8-4576-b168-a975922e67e5

Download Data

File	
	Brochures LEDiving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conform

Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.