

Product family datasheet

## LEDDriving BASIC R5W



Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage		Nominal luminous flux
LEDDriving BASIC $\triangleq$ R5W	0.96 W	12 V	0 W		55 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter	Lifespan B3	Lifespan Tc	Primary article identifier
LEDDriving BASIC $\triangleq$ R5W	$\pm 20\%$	19.0 mm	2000 hr	2000 hr	4052899463332   4052899414556   4052899463127   4052899414532

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDDriving BASIC $\triangleq$ R5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	12c61241-8e84-49d2-aad6-61ee9185fc4c   a74edd59-fe84-466f-9e9c-d76036657cbc   4deab8c0-c089-4d6a-90f4-3738f5af799e   e8c7bd92-d6cb-4cf2-9e8f-8360bae74918   eb08c6c5-5573-4254-af17-5f6a4f492b5f

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

