

PrevaLED Core Z6 Mini

Spot-, Down- and Wallmount Light Engines and Modules



Areas of application

- Spot lighting in shops and retail
- Down- and wall lighting in offices, corridors, meeting rooms, workplaces
- Decorative and functional lighting in hospitality, hotels, restaurants
- Functional lighting in public and commercial buildings

Product family benefits

- Easy integration thanks to very compact form factor
- Compatible with many Zhaga Book 11 accessories
- Easy cooling due to optimized efficiency and high maximum operation temperature
- High driver flexibility allows cost-effective and intelligent systems
- 5 year guarantee

Product family features

- Complete portfolio with varying luminous flux, color temperature, color rendering
- Available with color temperature: 2,700 K, 3,000 K, 3,500 K or 4,000 K
- High module efficacy: up to 145 lm/W at $T_p = 65^\circ\text{C}$
- No CoB assembly necessary with poke-in connector
- Chip technology from OSRAM Opto Semiconductors
- CE marked and UL listed
- Diameter: 35 x 4 mm with LES 13 (Zhaga book 11)
- Usable with SELV and DC (up to 60 V) control gears without additional insulation
- Lifetime (L80/B50): 60,000 h (temperature at $T_c = 65^\circ\text{C}$)

Product family datasheet

Equipment / Accessories

- System matches to OPTOTRONIC OTe, OT FIT, OTi DALI control gears
-

Application advice

For more detailed application information and graphics please see product datasheet.

Sales and Technical Support

Sales and Technical Support www.osram.com

References / Links

For more information on the multi-level guarantee and the terms and conditions of the guarantee visit

- ▶ www.osram.com/system-guarantee
-

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
