

## HMI DIGITAL 9000 W

HMI DIGITAL | Metal halide lamps, single-ended



### Areas of application

- Studio
- Stage
- TV

### Product family benefits

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

### Product family features

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Hot restart capability



Technical data

Electrical data

Nominal wattage	9000.00 W
Nominal voltage	160 V
Nominal current	56 A

Photometrical data

Nominal luminous flux	875000 lm
Color temperature	6000 K
Color rendering index Ra	90

Dimensions & weight

Diameter	80.0 mm
Length	380.0 mm

Lifespan

Lifespan	400 h
----------	-------

Additional product data

Base (standard designation)	GX38
-----------------------------	------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	06-03-2024
Primary Article Identifier	4062172001908
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	93767d86-c851-4107-80fa-6d9e2ea841f2

# Product datasheet

## Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172001908	HMI DIGITAL 9000 W	Shipping carton box 1	715 mm x 240 mm x 240 mm	41.18 dm <sup>3</sup>	2226.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.