## Product datasheet



# HMI DIGITAL 4000 W

HMI DIGITAL | Metal halide lamps, single-ended



#### Areas of application

- Studio
- Stage
- TV

### Product family benefits

- Suited for both analog and digital film production
- Robust stems, resulting in less breakage during transport
- Round moly-foil construction that evenly distributes heat and current extends for lamp longevity (6,000-18,000 W)
- Splash-proof carrying case is re-usable and allows lamps to be transported safely (6,000-18,000 W)

#### Product family features

- High CRI of >90
- UV-Stop (UVS)
- Color temperature of 6,000 K (daylight)
- Extremely bright light of up to 100 lumens/watt
- Hot restart capability



April 25, 2024, 01:42:07 HMI DIGITAL 4000 W

# Product datasheet

### Technical data

### **Electrical data**

Nominal wattage	400000 W	
Nominal voltage	200 V	
Nominal current	24 A	

### Photometrical data

Nominal luminous flux	387000 lm	
Color temperature	6000 К	
Color rendering index Ra	90	

# Dimensions & weight

Diameter	7500 mm
Length	2500 mm

### Lifespan

Lifespan	500 h

### Additional product data

Deep (stead and design stice)	670
Base (standard designation)	638

### **Environmental information**

# Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)

Date of Declaration	07-03-2024	
Primary Article Identifier	4052899984301	
Candidate List Substance 1	No declarable substances contained	
Declaration No. in SCIP database	No declarable substances contained	

# Product datasheet

#### Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, HMI lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899984301	HMI DIGITAL 4000 W	Shipping carton box 1	342 mm x 153 mm x 145 mm	7.59 dm <sup>3</sup>	569.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.