

Product datasheetP RF CLAS P DIM 280 W/827 E14

PARATHOM Retrofit CLASSIC P DIM | Dimmable LED lamps, classic bulb shape



 Perfect for decorative installations Domestic applications General illumination Outdoor use in outdoor luminaires only (minimum IP65)

 Design, dimensions, luminous flux comparable to an incandescent lamp Very low energy consumption Robust against vibrations Lamps with innovative LED "filament" technology Instant 100 % light, no warm-up time Can be easily fitted instead of ordinary light bulbs





Page 1 of 4

Product datasheet

Technical data

Electrical data

| Operating frequency | 5060 Hz |
|--|---------|
| Nominal current | 13 mA |
| Claimed equiv. conventional lamp power | 25 W |


Photometrical data

| Light color (designation) | Warm White |
|---------------------------|------------|
| Luminous flux | 250 lm |

Light technical data

| Beam angle | 320 ° |
|------------|-------|
| | |

Dimensions & weight



| Overall length | 78.00 mm |
|----------------|----------|
| Product weight | 13.00 g |

Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|---------------------------|-----------|
|---------------------------|-----------|

Lifespan

| Lumen maintenance at end of service life | 0.7 |
|--|-----|
|--|-----|

Additional product data

| Mercury content | 0.0 mg |
|-----------------------------------|---------|
| Mercury-free | Yes |
| Design / version | Frosted |
| Appropriate disposal acc. to WEEE | Yes |

Product datasheet

| Product remark | Dimmable (with many common dimmers, see also | |
|----------------|--|--|
| | www.ledvance.com/dim) | |

Certificates & standards

| Energy efficiency class | F |
|-------------------------|----------------|
| Energy consumption | 3.00 kWh/1000h |

Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) | | | | |
|---|---------------|--|--|--|
| Date of Declaration 18-04-2022 | | | | |
| Primary Article Identifier | 4058075591134 | | | |
| Declaration No. in SCIP database | In work | | | |

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|----------------------------------|--|--------------------------------------|----------------------|--------------|
| 4058075591134 | P RF CLAS P DIM 280 W/827 E14 | Shipping carton box 10 Pieces Folding carton box | 240 mm x 101 mm x 108 mm | 2.62 dm ³ | 288.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Product datasheet

OSRAM is distribution partner of LEDVANCE of LAMPS



OSRAM GmbH Marcel-Breuer-Strasse 6 80807 Munich, Germany