

## 64650 50W 22.8V 40/CS 1/SKU



### Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

### Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	54257
Product Name	64650 50W 22.8V 40/CS 1/SKU
Application	Projector, Microfilm, Microscope, Studio

Electrical data

Nominal Wattage	50 W
Nominal Voltage	22.8 V
Type of Current	AC

Light technical data

Luminous Flux	1150 lm
Light Center Length - LCL (in)	1.17 in
Light Center Length - LCL (mm)	30 mm
Color Temperature	3100 K
Color Rendering Index	100
Average Rated Life	1000 h


Physical attributes

Base	G6.35
Maximum Overall Length (in)	1.716 in
Maximum Overall Length (mm)	44 mm
Length l (in)	1.716 in
Length l (mm)	44 mm
Diameter d (in)	0.512 in
Diameter d (mm)	13.00 mm
Distance a (in)	1.170 in
Distance a (mm)	30 mm
Filament Dimensions Length (in)	0.1950 in
Filament Dimensions Length (mm)	5 mm
Filament Dimensions Width (in)	0.078 in
Filament Dimensions Width (mm)	2 mm

Additional product data

Operating Position	Any
--------------------	-----

Product datasheet



Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54257	4008321107138	Folding box (SKU)	1		
54257	4008321107145	Shipping box (Case)	40	5.9 in x 4.4 in x 4.6 in	0.8 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.