

EVC 64657 HLX 250W 24V 40/CS 1/SKU



Product features and benefits

- Precise filament alignment with patented quartz pinch technology
- OSRAM HLX lamps provide 10% higher luminous efficacy over standard halogen
- Instant on and nearly constant luminous flux over the life of the lamp
- Dimmable

Areas of application

- Microscopy
- Laboratory & Analysis
- UV curing
- Fiber Illumination
- Surgical & Dental Overhead
- Club & Disco

Technical data

General product information

Product Number	54255
Product Name	EVC 64657 HLX 250W 24V 40/CS 1/SKU
Family Brand Name	XENOPHOT (HLX)
Application	Projector, Microfilm, Microscope, Studio
LIF Code	M/33
Product Remark	– s (Operating Position) = Vertical, base down

Electrical data

Nominal Wattage	250 W
Nominal Voltage	24 V
Type of Current	AC

Light technical data

Luminous Flux	9000 lm
Light Center Length - LCL (in)	1.287 in
Light Center Length - LCL (mm)	33 mm
Color Rendering Index	100
Average Rated Life	300 h

Physical attributes

Base	G6.35
Bulb Shape	T12
Maximum Overall Length (in)	2.145 in
Maximum Overall Length (mm)	55 mm
Length l (in)	2.145 in
Length l (mm)	55 mm
Diameter d (in)	0.551 in
Diameter d (mm)	14.00 mm
Distance a (in)	1.287 in
Distance a (mm)	33 mm
Filament Dimensions Length (in)	0.1560 in
Filament Dimensions Length (mm)	4 mm
Filament Dimensions Width (in)	0.312 in
Filament Dimensions Width (mm)	8 mm

Additional product data

Product datasheet

Operating Position	s 90
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54255	4050300012001	Folding box (SKU)	1		
54255	4050300890821	Shipping box (Case)	40	5.7 in x 4.2 in x 4.8 in	0.6 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.