

HTI 150 W 12/CS 1/SKU



Product features and benefits

- Robust design with eXtreme Seal (XS) technology on some types, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency

Areas of application

- Concert lighting
- Club & Disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Product datasheet

Technical data

General product information

Product Number	54078			
Product Name	HTI 150 W 12/CS 1/SKU			
Family Brand Name	нті			
Application	Entertainment and Effect Lighting, Fiber Optic			
Product Remark	- Lamp arc needs to be in horizontal operating position.			

Electrical data

Nominal Wattage	150 W
Nominal Voltage	95 V
Current (A)	1.8 A
Type of Current	AC

Light technical data

Luminous Flux	9500 lm		
Average Luminance (cd/cm2)	5000 cd/cm2		
Light Center Length - LCL (mm)	30 mm		
Color Temperature	6500 K		
Color Rendering Index	70		
Average Rated Life	750 h		

Physical attributes

Base	GY9.5
Bulb Shape	T6
Maximum Overall Length (mm)	46 mm
Length I (mm)	46 mm
Length I max. (mm)	46 mm
Diameter d (in)	0.787 in
Diameter d (mm)	20.00 mm
Distance a (mm)	30 mm
Electrode Gap - cold (mm)	5 mm

Additional product data

Operating Position	Any	
Maximum Base Temperature (°C)	230 C	
Cooling	Convection	

Product datasheet

Hot Restart	No
Lamp Type	SINGLE END

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54078	4050300301402	Folding box (SKU)	1	1.5 in x 1.5 in x 2.9 in	
54078	4050300301419	Shipping box (Case)	12	9.3 in x 3.3 in x 3.3 in	0.6 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.