

HTI 152 W 12/CS 1/SKU



Product features and benefits

- Robust design with eXtreme Seal (XS) technology on some types, allowing up to 450°C at the pinch seal
- Consistent lumen output over the life of the lamp
- Higher luminous efficacy than conventional HID lamps provides higher fixture efficiency

Areas of application

- Concert lighting
- Club & Disco
- Stage and theatre
- Studio, TV and film
- Architecture & Architainment

Technical data

General product information

Product Number	54079		
Product Name	HTI 152 W 12/CS 1/SKU		
Family Brand Name	нті		
Application	Entertainment and Effect Lighting, Fiber Optic		

Electrical data

Nominal Wattage	152 W
Nominal Voltage	90 V
Current (A)	1.8 A
Type of Current	AC

Light technical data

Average Luminance (cd/cm2) 4200 cd/cm2	
Light Center Length - LCL (mm)	30 mm
Color Temperature	5000 К
Average Rated Life	2000 h

Physical attributes

Base	GY9.5
Bulb Shape	Т6
Maximum Overall Length (mm)	48 mm
Length l (mm)	48 mm
Length l max. (mm)	48 mm
Diameter d (in)	0.787 in
Diameter d (mm)	20.00 mm
Distance a (mm)	30 mm
Electrode Gap - cold (mm)	6.8 mm

Additional product data

Operating Position	Any
Maximum Base Temperature (°C)	230 C
Cooling	Convection
Hot Restart	No

Packaging Information

Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
54079	4050300461519	Folding box (SKU)	1		
54079	4050300461526	Shipping box (Case)	12	6.5 in x 3.3 in x 6.5 in	0.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.