


64361 HLX-A 150-15 PK30D 100/CS 1/SKU



Product features and benefits

- Low maintenance costs due to long lamp life
- Reliable and consistent light output enhances visibility over the life of the lamp
- FAA approved in conjunction with many OEM fixtures
- Durable construction provides resistance to the effects of vibration
- Broad product portfolio for runway, taxiway, and approach lighting
- IR radiation provides guidance in low visibility conditions
- Flicker-free operation
- Ability to reduce light output when needed
- Mercury-free

Areas of application

- Airfield lighting

Product datasheet

Technical data

General product information

Product Number	59077
Product Name	64361 HLX-A 150-15 PK30D 100/CS 1/SKU
Application	Airfield/Airport
LIF Code	J1/83

Electrical data

Nominal Wattage	150 W
Nominal Voltage	22.7 V
Current (A)	6.6 A

Light technical data

Light Center Length - LCL (in)	0.787 in
Light Center Length - LCL (mm)	20 mm
Average Rated Life	1500 h

Physical attributes

Base	PK30D
Maximum Overall Length (in)	1.969 in
Maximum Overall Length (mm)	50 mm
Diameter d (in)	0.531 in
Diameter d (mm)	13.50 mm
Filament	C BAR 6
Filament Dimensions Length (in)	0.1420 in
Filament Dimensions Length (mm)	3.6 mm
Filament Dimensions Width (in)	0.28 in
Filament Dimensions Width (mm)	7.1 mm

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
59077	4008321345691	Folding box (SKU)	1	1.3 in x 1.5 in x 2.7 in	0.1 lb
59077	10046135590778	Shipping box (Case)	100	13.4 in x 7.5 in x 6.1 in	5 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.