
TP22HCE 160CM16GAUL1659 40/CS 10/SKU

Product features and benefits

- Ceramic housings designed specifically for high temperature halogen and metal halide applications
- High quality contact materials for optimal mechanical and electrical properties
- UL recognized and CE certified

Areas of application

- Halogen Fixtures
- Metal Halide Fixtures
- Halogen Instrumentation
- Halogen Equipment

Product datasheet

Technical data

General product information

| | |
|----------------|--------------------------------------|
| Product Number | 69018 |
| Product Name | TP22HCE 160CM16GAUL1659 40/CS 10/SKU |

Electrical data

| | |
|---------------------|--------|
| Maximum Wattage (W) | 1000 W |
| Maximum Voltage (V) | 250 V |

Physical attributes

| | |
|------------------|----------------------|
| Body Material | Ceramic Steatite |
| Contact Material | Silver Plated Nickel |
| Wire Type | UL 1659 |
| Wire Gauge (AWG) | 16 AWG |

Additional product data

| | |
|------------------------------------|-------|
| Maximum Operating Temperature (°C) | 250 C |
| Rohs Compliant | Yes |

Packaging Information

| Product number | EAN/UPC | Packaging | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 69018 | 4008321485571 | Shipping box (Case) | 10 | 10.1 in x 7.4 in x 3.1 in | 4 lb |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.