

## HMI 24000W/DXS 1/CS 1/SKU



### Product features and benefits

- High intensity light providing true color performance with a CRI>90
- Longer life with heat dissipating round moly-foil design on lamps  $\geq 6000\text{W}$
- Mechanically robust with eXtreme Seal (XS) technology, up to  $450^{\circ}\text{C}$  at the pinch seal
- Capable of hot restrike ignition
- High color stability with average changes in color temperature during lamp life only  $1^{\circ}\text{K/hr}$
- Dimmable down to 40% with stable color using many electronic ballasts
- High energy efficiency providing up to 100 LPW
- Compression sealed base provides enhanced durability

### Areas of application

- Studio, TV and film
- Professional Photography
- Solar Simulation

Technical data

General product information

|                   |  |
|-------------------|--|
| Product Number    | 54325  |
| Product Name      | HMI 24000W/DXS 1/CS 1/SKU  |
| Family Brand Name | HMI  |
| Application       | Film, TV & Video Production. Studio Lighting   |
| Product Remark    | <ul style="list-style-type: none"><li>- DXS=Double-ended eXtreme Seal technology</li><li>- p (Operating Position) = Horizontal</li><li>- Optimized lamp eXtreme Seal (XS) technology to withstand interior base temperatures of up to 450 degrees celsius.</li></ul> |

Electrical data

|                 |         |
|-----------------|---------|
| Nominal Wattage | 24000 W |
| Nominal Voltage | 280 V   |
| Current (A)     | 86 A    |
| Type of Current | AC      |

Light technical data

|                          |            |
|--------------------------|------------|
| Luminous Flux            | 2300000 lm |
| Luminous Efficacy (lm/W) | 95 lm/W    |
| Average Rated Life       | 375 h      |

Physical attributes

|                           |          |
|---------------------------|----------|
| Base                      | S30      |
| Bulb Shape                | T26      |
| Length l1 (in)            | 83 in    |
| Length l1 (mm)            | 500 mm   |
| Diameter d (in)           | 3.268 in |
| Diameter d (mm)           | 83.00 mm |
| Electrode Gap - cold (mm) | 50 mm    |

Additional product data

|                               |                           |
|-------------------------------|---------------------------|
| Operating Position            | HORIZONTAL +/- 15 Degrees |
| Maximum Base Temperature (°C) | 450 C                     |
| Cooling                       | CONVECTION                |
| Hot Restart                   | Yes                       |

Packaging Information

Product datasheet

| Product number | EAN/UPC       | Packaging           | Quantity | Outside dimensions L x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 54325          | 4008321355805 | Shipping box (Case) | 1        | 24.2 in x 5.9 in x 7.7 in    | 3.6 lb       |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.