

HBO 2002W/37V/MA 4/CS 1/SKU



Product features and benefits

- High spectral intensity with peak irradiance at 365nm wavelength, making it ideal for microlithography
- Ceramic housings designed specifically for high temperature halogen and metal halide applications for optimal exposure and throughput
- Designed for long lasting performance
- Qualified with Canon

Areas of application

- Semiconductor

Technical data

General product information

| Product Number | 69199 | | |
|-------------------|--|--|--|
| Product Name | HBO 2002W/37V/MA 4/CS 1/SKU | | |
| Family Brand Name | НВО | | |
| Application | Semiconductor | | |
| Product Remark | Anode Base with cable connection (M 8). This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp. Lamp should not be ignited more than ten times over lifetime. Cathode Base with cable connection (M 8). The average rated life of this lamp depends on the operating mode (initial power setting). | | |

Electrical data

| Nominal Wattage | 2000 W |
|-----------------|--------|
| Nominal Voltage | 37 V |
| Current (A) | 54 A |
| Type of Current | DC |

Light technical data

| Radiant intensity 365 ± 2.5nm (mW/sr) | 4200 | |
|---------------------------------------|----------|--|
| Light Center Length - LCL (mm) | 138.5 mm | |
| Average Rated Life | 750 h | |

Physical attributes

| Base Anode SF27/35 | | | |
|--------------------------------------|-------------|--|--|
| Base Cathode | SFa27-10/35 | | |
| Maximum Overall Length (mm) 292 mm | | | |
| Length l1 (mm) | 292 mm | | |
| Length l1 max. (mm) | 292 mm | | |
| Diameter d (in) | 2.441 in | | |
| Diameter d (mm) | 62.00 mm | | |
| Distance a (mm) | 138.5 mm | | |
| Electrode Gap - cold (mm) | 3 mm | | |

Additional product data

| Operating Position | Vertical, anode down |
|--------------------|----------------------|
| | |

Product datasheet

| Maximum Base Temperature (°C) | 200 C | |
|-------------------------------|--------------|--|
| Cooling Forced Base | | |
| Lamp Type | DOUBLE ENDED | |

Packaging Information

| Product number | EAN/UPC | Packaging | Quantity | Outside dimensions l x w x h | Gross weight |
|----------------|---------------|---------------------|----------|------------------------------|--------------|
| 69199 | 4050300628240 | Folding box (SKU) | 1 | 23.2 in x 12.6 in x 9.1 in | 5.9 lb |
| 69199 | 4050300732572 | Folding box | 4 | | |
| 69199 | 4050300628257 | Shipping box (Case) | 4 | 31.5 in x 23.6 in x 32.5 in | 41.8 lb |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.