

HBO 1002W/47V/NEL 1/CS 1/SKU



Product features and benefits

- High spectral intensity with peak irradiance at 365nm wavelength, making it ideal for microlithography
- Ceramic housings designed specifically for high temperature halogen and metal halide applications for optimal exposure and throughput
- Designed for long lasting performance
- Qualified with Nikon

Areas of application

- Semiconductor

Product datasheet

Technical data

General product information

Product Number	69273
Product Name	HBO 1002W/47V/NEL 1/CS 1/SKU
Family Brand Name	HBO
Application	Semiconductor
Product Remark	<ul style="list-style-type: none">- Anode Base=Sleeve base with cable connection (M5)- Cathode Base=Sleeve base with M 6 thread.

Electrical data

Nominal Wattage	750 W
Nominal Voltage	47 V
Current (A)	16 A
Type of Current	DC

Light technical data

Radiant intensity in 350-450 nm range (mW/sr)	8300 mW/sr
Radiant Power in 350-450 nm range (W)	82 W
Light Center Length - LCL (mm)	78.5 mm
Average Rated Life	2500 h

Physical attributes

Base Anode	SFaX14-5/21
Base Cathode	SFc15-6/25
Maximum Overall Length (mm)	190 mm
Length l1 (mm)	190 mm
Length l1 max. (mm)	190 mm
Diameter d (in)	1.102 in
Diameter d (mm)	28.00 mm
Distance a (mm)	78.5 mm
Electrode Gap - cold (mm)	3 mm

Additional product data

Operating Position	Vertical, anode down
Maximum Base Temperature (°C)	200 C
Cooling	Convection
Lamp Type	DOUBLE ENDED

Product datasheet

Packaging Information

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69273	4050300412610	Shipping box (Case)	1	13 in x 4.3 in x 4.5 in	1.7 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

OSRAM does not accept liability for errors, changes and omissions.