

## HBO 201W/HS-D2 10/CS 1/SKU



### Product features and benefits

- High spectral intensity with peak irradiance at 365nm wavelength, making it ideal for microlithography
- Ceramic housings designed specifically for high temperature halogen and metal halide applications for optimal exposure and throughput
- Designed for long lasting performance
- Qualified with TEL

### Areas of application

- Semiconductor

## Product datasheet

### Technical data

#### General product information

Product Number	69168
Product Name	HBO 201W/HS-D2 10/CS 1/SKU
Family Brand Name	HBO
Application	Semiconductor
Product Remark	<ul style="list-style-type: none"><li>- This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp.</li><li>- 2000hr warranty against non-passive lamp failure.</li></ul>

#### Electrical data

Nominal Wattage	201 W
Nominal Voltage	25 V
Current (A)	8 A
Type of Current	DC

#### Light technical data

Average Rated Life	1000 h
--------------------	--------

#### Physical attributes

Base Anode	SFcX32-22
Base Cathode	SFcX12-4/15
Maximum Overall Length (mm)	150 mm
Length l1 (mm)	150 mm
Length l1 max. (mm)	150 mm
Diameter d (in)	0.787 in
Diameter d (mm)	20.00 mm
Electrode Gap - cold (mm)	2 mm

#### Additional product data

Operating Position	Vertical, anode up
Maximum Base Temperature (°C)	230 C
Cooling	Convection
Lamp Type	DOUBLE ENDED

### Packaging Information

## Product datasheet

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions L x w x h	Gross weight
69168	4050300591940	Folding box (SKU)	1	8.1 in x 3.6 in x 2.3 in	0.6 lb
69168	4050300591957	Shipping box (Case)	10	18.5 in x 8.5 in x 5.1 in	5.9 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

OSRAM does not accept liability for errors, changes and omissions.