

# XBO 4000W/DHP L 1/CS 1/SKU



## Product features and benefits

- Extremely high luminance for digital cinema projection
- Color temperature approximately 6000K simulates daylight
- Continuous spectrum in the visible range
- High color rendering > 95
- High arc stability
- DC operation
- Hot restart

## Areas of application

- Digital Projection
- Film Projection
- Spotlights
- Searchlights
- Solar Simulation

# Product datasheet

## Technical data

## **General product information**

Product Number	69049			
Product Name	XBO 4000W/DHP L 1/CS 1/SKU			
Family Brand Name	XBO			
Application	Digital Cinema Projection			
Product Remark	<ul> <li>OFR=Ozone Free</li> <li>s (Operating Position) = Vertical, base down</li> <li>p (Operating Position) = Horizontal</li> <li>This lamp has positive pressure even when cold. Please read safety/warning instructions before using this lamp.</li> </ul>			

## **Electrical data**

Nominal Wattage	4200 W
Nominal Voltage	33 V
Current (A)	128 A
Current Control Range (A)	95-137 A
Type of Current	DC

# \_ Light technical data

Light Center Length - LCL (mm)	123 mm
Average Rated Life	1300 h
Warranty Hours (hr)	1300 hrs
Service Warranty Lifetime (hr)	1500 hrs

## **Physical attributes**

Base Anode	SFaX27-14x71
Base Cathode	SFc27-16/55
Bulb Shape	T60
Maximum Overall Length (mm)	345 mm
Length l1 max. (mm)	345 mm
Diameter d (in)	2.362 in
Diameter d (mm)	60.00 mm
Distance a (mm)	123 mm
Electrode Gap - cold (mm)	6.2 mm

## Additional product data

## Product datasheet

Maximum Base Temperature (°C)	230 C
Cooling	Required

## **Packaging Information**

Product number	EAN/UPC	Packaging	Quantity	Outside dimensions l x w x h	Gross weight
69049	4062172030403	Shipping box (Case)	1	19.7 in x 8 in x 8 in	3.2 lb

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

OSRAM does not accept liability for errors, changes and omissions.