


ONYX COPILOT USB

Flexible LED reading light



20 lm

Pleasantly warm and glare-free light



37 cm

370 mm neck length powered via USB



Multifunctional use

This stylish reading light is suitable for all vehicles with USB connection



Precisely illuminating vehicle interiors

With its elegant and dynamic design, the ONYX COPILOT LED reading light achieves seamless integration into vehicle interiors. With its high flexibility, the reading light has a wide range of options for illuminating specific areas of the vehicle interior. The neck of the light is made of matt black silicon rubber and can be individually adjusted. The LED lifetime of ONYX COPILOT is extremely long: up to 20,000 hours! The Luminaire can be switched on/off and remain connected permanently. OSRAM provides a 2 year guarantee for this stylish light.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	Flexible LED reading light
---	----------------------------

General Product Information

Global order reference	ONYX COPILOT USB
------------------------	------------------

Photometric Data

Color temperature	3200 K
Nominal luminous flux	20 lm
Light color LED	Warm white

Physical Attributes & Dimensions



Product weight	58.00 g
Length	394.0 mm
Width	25.0 mm
Height	9.5 mm

Colors & materials

Base color	Black
------------	-------

Lifetime Data

Guarantee	2 years
-----------	---------

Additional product data

Connector to lamp	USB
-------------------	-----

Capabilities

Product datasheet

Technology	LED ¹⁾
------------	-------------------

¹⁾ Light-emitting diode application

Certificates & standards

Type of protection	IP20
Standards	CE

Environmental & Regulatory Information




Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Primary article identifier	4052899601000
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	cfe381e9-de61-47be-8ff4-79f99a462d05

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899601000	ONYX COPILOT	Folding carton box 1	110 mm x 35 mm x 290 mm	1.12 dm ³	139.00 g
4052899601017	ONYX COPILOT	Shipping carton box 4	149 mm x 118 mm x 302 mm	5.31 dm ³	674.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 User instruction LED ONYX COPILOT USB
 User instruction GPRS_Safety symbols instructions
 ref_pim_amsproduct360degreeimages ONYX Copilot USB

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Product datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.