

LEDDriving SL P13W

Ideal replacement for any vehicle



High color temperatures of up to 6,000 K

Faster signals provide more reaction time for drivers behind you



High brightness

Faster signals provide more reaction time for drivers behind you



Replaces conventional P13W lamps

Upgrade to LED with simple plug & play replacement



Suitable LED replacement for P13W

These LEDDriving SL retrofit lamps were specially developed for a suitable replacement of conventional P13W lamp types. Perfect for a multitude of applications, OSRAM LEDDriving SL illuminate vehicle exteriors with high color temperatures of up to 6,000 K. Thanks to their homogeneous light distribution, illumination is non-selective. OSRAM LED retrofits come with easy plug-and-play replacement, long life spans, low energy consumption – and 100% more style. OSRAM provides a 4-year guarantee for this product. For precise guarantee conditions please refer to www.osram.com/am-guarantee. Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Product datasheet

Technical data

Product information

Order reference	3828CW
Product type (off-road vs. on-road)	Off-road \pm P13W
Application (Category and Product specific)	Mainly used for daytime running light applications

Electrical data

Power input	1.98 W
Nominal voltage	12.0 V
Nominal wattage	1.80 W
Test voltage	13.5 V
Power input tolerance	± 10 %

Photometrical data

Luminous flux	130 lm
Luminous flux tolerance	± 15 %
Color temperature	6000 K
Light color LED	Cool white

Dimensions & weight

Diameter	23.0 mm
Product weight	10.50 g
Length	48.3 mm

Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

Additional product data

Base (standard designation)	PG18.5D-1
-----------------------------	-----------

Capabilities

Technology	LED
------------	-----

Certificates & standards

ECE category	
--------------	--

Product datasheet

Country specific categorizations


Order reference	3828CW
-----------------	--------

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899604988	LEDiving STANDARD \triangleq P13W	Folding carton box 1	34 mm x 35 mm x 58 mm	0.07 dm ³	13.90 g
4052899604995	LEDiving STANDARD \triangleq P13W	Shipping carton box 10	178 mm x 76 mm x 67 mm	0.91 dm ³	162.00 g
4062172035866	LEDiving STANDARD \triangleq P13W	Unpacked 1	- x - x -		
4062172022750	LEDiving STANDARD \triangleq P13W	Shipping carton box 300	553 mm x 300 mm x 333 mm	55.24 dm ³	3621.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 Brochures Sales Folder LEDiving replacement lamps (EN)

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM