

# LEDDriving HL H7 Gen2



**Cool White color temperature of 6,000 K**

Better visibility thanks to daylight effect



**Superior brightness**

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner



**Very compact LED replacement for conventional H7 high and low beam lamps**

Reduced glaring thanks to an optimized light distribution



With a color temperature of 6,000 K and a very compact design, the OSRAM LEDDriving HL retrofits provide an easy solution to upgrade car headlights with cool white LED light – providing a stylish look as well as superior brightness. The LED high and low beam lamps by OSRAM as replacement of conventional H7 lamps. With the latest LED technology and very compact design, these new lamps allow a high compatibility and an easy installation for an even wider range of car models. LEDDriving HL lamps are 12 V and 24 V compatible. The pair of lamps comes with a 5-year OSRAM guarantee and with a long service life. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

## Product family datasheet

### Technical data

Product description	Product information			Electrical data		
	Order reference	Application (Category and Product specific)	Product type (off-road vs. on-road)	Power input	Nominal voltage	Nominal wattage
LEDriving HL $\triangleq$ H7 Gen2	67210CW	Mainly used for headlight/ fog light applications	Off-road $\triangleq$ H7	18.59 W	12 /24 V	16.90 W



Product description	Test voltage	Photometrical data		Dimensions & weight	Lifespan	
		Luminous flux	Luminous flux tolerance	Diameter	Lifespan B3	Lifespan Tc
LEDriving HL $\triangleq$ H7 Gen2	13.5 V	1215 lm	$\pm 15\%$	13.8 mm	2500 h	5000 h

Product description	Additional product data	Capabilities	Certificates & standards
	Base (standard designation)	Technology	ECE category
LEDriving HL $\triangleq$ H7 Gen2	PX26d	LED	

## Product family datasheet

---

### Download Data

File	
	User instruction LEDiving HL
	Brochures Sales Folder LEDiving replacement lamps (EN)

#### Legal advice

Detailed guarantee terms can be found at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee).

These products do not have ECE approval. This means they must not be used on public roads in any exterior application. Use on public roads leads to cancellation of operating license and loss of insurance coverage. Several countries do not allow sale and use of these products. Please contact your local distributor for information on the availability in your country.

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

