

# LEDDriving FL H10

LED replacement for conventional fog lamps



**Cool White color temperature of 6,000 K**

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



**Superior brightness**

More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



**Ultra compact LED replacement for conventional H10 fog lamps as socket solution**

Easy installation with optimized compatibility



### New OSRAM LED fog lamps to increase safety and performance

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps: With its ultra compact dimensions, the OSRAM LEDDriving FL provides optimized compatibility as well as easy plug & play installation. Upgrading with state-of-the-art LED technology and a color temperature of 6,000 K for a stylish cool white look as well as improved visibility. These LED products offer a perfect color match with xenon and LED headlights and are for conventional H10 fog lamps. A pair of new LEDDriving FL lamps, comes with a 3-year OSRAM guarantee as well as with a long service life by less energy consumption. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

# Product datasheet

## Technical data

### Product information

Product type (off-road vs. on-road)	Off-road $\triangleq$ H10
Application (Category and Product specific)	Mainly used for fog light applications

### General Product Information

Global order reference	9745CW
------------------------	--------

### Electrical Data

Power input	9.43 W
Test voltage	13.5 V
Power input tolerance	$\pm 15$ %
Nominal wattage	8 W
Nominal voltage	12.0 V

### Photometric Data

Color temperature	6000 K
Nominal luminous flux	720 lm
Luminous flux tolerance	$\pm 15$ %
Light color LED	Cool white

### Physical Attributes & Dimensions

Product weight	33.30 g
Length	73.1 mm
Lamp base	PY20d
Diameter	17.2 mm

### Lifetime Data

Lifespan Tc	5000 hr
Guarantee	4 years
Lifespan B3	2500 hr

### Capabilities

Technology	LED
------------	-----

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
---

## Product datasheet


Date of declaration	09-07-2024
Primary article identifier	4052899605060   4062172401913   4062172033329
Declaration no. in SCIP database	In work

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899605077	LEDriving FL $\cong$ H10		- x - x -	6.46 dm <sup>3</sup>	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 Brochures LEDriving Retrofits - Exchange overview (EN)

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information. Detailed guarantee terms can be found at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee).

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



# OSRAM