

## PL-LIN-Z5 275-840 70X20-LV

PrevaLED Linear G5 | Linear Light Engines



### Areas of application

- Office
- Industry

### Product family benefits

- Slim luminaire design by small and flexible form factor
- High homogeneity thanks to small LED pitch
- High voltage (HV) for serial connection
- Low voltage (LV) for parallel connection
- High voltage (HV) for non-isolated, low voltage (LV) for SELV operation
- Adjustable luminous flux, efficacy and lifetime
- Direct the light where it's needed while using PrevaLED Linear Optics



## Product datasheet

---

### Product family features

- Module efficacy: up to 193 lm/W
- Available with luminous flux: 275 lm on 70 mm
- Available with luminous flux: 1,100 lm or 2,000 lm on 280 mm
- Available with luminous flux: 2,000 lm, 4,000 lm on 560 mm
- Available with luminous flux: 4,400 lm on 1,120 mm
- Available with luminous flux: 5,500 lm on 1,400 mm
- Available with color temperature: 3,000 K, 4,000 K or 6,500 K
- High initial color consistency:  $\leq 3$  SDCM
- Average lifetime (L80 B50):  $> 70,000$  h (temperature at  $T_c = 50$  °C)
- CE marked, ENEC certified; UL listed

### Technical data

#### Electrical data

Nominal voltage	23.5 V
Nominal current	0.062 A
Nominal wattage	1.50 W
Rated wattage	1.50 W
Type of current	DC

#### Photometrical data

Light color LED	White
Luminous efficacy	184 lm/W
Standard deviation of color matching	≤3 sdcn
Color temperature	4000 K
Color rendering index Ra	>80
Rated peak intensity	91 cd
Nom. useful luminous flux 120°	275 lm
Rated useful luminous flux 120°	271 lm
Total useful luminous flux	275 lm


#### Light technical data

Beam angle	120 °
Starting time	< 0.1 s
Warm-up time (60 %)	< 2.00 s
Rated beam angle (half peak value)	120.00 °

#### LED module information

Number of LEDs per module	9
---------------------------	---

## Dimensions & weight



Product weight	5.00 g
Length	70.0 mm
Width	20.0 mm
Height	5.00 mm

## Temperatures & operating conditions

Performance temp. acc. to IEC 62717	50 °C
Temperature range in operation at Tc point	-20...75 °C
Maximum temperature at tc test point	75 °C
Temperature range at storage	-30...85 °C
Ambient temperature range	-20...+75 °C

## Lifespan

Number of switching cycles	100000
Rated lamp life time	50000 h
Lumen main.fact.at end of nom.life time	0.80
Nominal lamp life time	50000 h

## Capabilities

Dimmable	Yes
----------	-----

## Certificates & standards





Energy consumption	2 kWh/1000h
Energy efficiency class	A++
Standards	CE/ENEC
Type of protection	IP20

## Product datasheet

### Logistical data

Commodity code	854140100000
----------------	--------------

### Download Data

File
 Product Datasheet PL LIN G5 DS 190220 (EN)
 Certificates PL BA ENEC 40031612 161219
 Declarations of conformity PL LIN Z5 CE 3812352 290719
 CAD data 3-dim PL LIN Z6 275 70x20 LV CADPDF 240220

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899618015	PL-LIN-Z5 275-840 70X20-LV	Shipping carton box 120	382 mm x 173 mm x 121 mm	8.00 dm <sup>3</sup>	811.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.