

## PL-LIN-Z5 2000-840 280X20-LV/HV

PrevaLED Linear G5 | Linear Light Engines



### Areas of application

- Office
- Industry

### Product family benefits

- Slim luminaire design by small and flexible form factor
- High homogeneity thanks to small LED pitch
- High voltage (HV) for serial connection
- Low voltage (LV) for parallel connection
- High voltage (HV) for non-isolated, low voltage (LV) for SELV operation
- Adjustable luminous flux, efficacy and lifetime
- Direct the light where it's needed while using PrevaLED Linear Optics



## Product datasheet

---

### Product family features

- Module efficacy: up to 193 lm/W
- Available with luminous flux: 275 lm on 70 mm
- Available with luminous flux: 1,100 lm or 2,000 lm on 280 mm
- Available with luminous flux: 2,000 lm, 4,000 lm on 560 mm
- Available with luminous flux: 4,400 lm on 1,120 mm
- Available with luminous flux: 5,500 lm on 1,400 mm
- Available with color temperature: 3,000 K, 4,000 K or 6,500 K
- High initial color consistency:  $\leq 3$  SDCM
- Average lifetime (L80 B50):  $> 70,000$  h (temperature at  $T_c = 50$  °C)
- CE marked, ENEC certified; UL listed

### Technical data

#### Electrical data

Nominal voltage	43.1 V
Nominal current	0.275 A
Nominal wattage	11.80 W
Rated wattage	11.80 W
Type of current	DC

#### Photometrical data

Light color LED	White
Luminous efficacy	175 lm/W
Standard deviation of color matching	≤3 sdcn
Color temperature	4000 K
Color rendering index Ra	>80
Rated peak intensity	660 cd
Nom. useful luminous flux 120°	2000 lm
Rated useful luminous flux 120°	2072 lm
Total useful luminous flux	2072 lm


#### Light technical data

Beam angle	120 °
Starting time	< 0.1 s
Warm-up time (60 %)	< 2.00 s
Rated beam angle (half peak value)	120.00 °

#### LED module information

Number of LEDs per module	72
---------------------------	----

## Dimensions & weight



<b>Product weight</b>	20.00 g
<b>Length</b>	280.0 mm
<b>Width</b>	20.0 mm
<b>Height</b>	5.0 mm

## Temperatures & operating conditions

<b>Performance temp. acc. to IEC 62717</b>	50 °C
<b>Temperature range in operation at Tc point</b>	-20...75 °C
<b>Maximum temperature at tc test point</b>	75 °C
<b>Temperature range at storage</b>	-30...85 °C
<b>Ambient temperature range</b>	-20...+75 °C

## Lifespan

<b>Number of switching cycles</b>	100000
<b>Rated lamp life time</b>	50000 h
<b>Lumen main.fact.at end of nom.life time</b>	0.80
<b>Nominal lamp life time</b>	50000 h

## Capabilities

<b>Dimmable</b>	Yes
-----------------	-----

## Certificates & standards





<b>Energy consumption</b>	12 kWh/1000h
<b>Energy efficiency class</b>	A++
<b>Standards</b>	CE/ENEC/VDE
<b>Type of protection</b>	IP20

## Product datasheet

### Logistical data

Commodity code	854140100000
----------------	--------------

### Download Data

File
 Product Datasheet PL LIN G5 DS 190220 (EN)
 Certificates PL BA ENEC 40031612 161219
 Declarations of conformity PL LIN Z5 CE 3812352 290719
 CAD data 3-dim PL LIN Z5 Z6 2000 280x20 LV HV CADPDF 240220

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899607163	PL-LIN-Z5 2000-840 280X20-LV/HV	Shipping carton box 240	588 mm x 380 mm x 125 mm	27.93 dm <sup>3</sup>	5377.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.