

## PL-LIN-Z5 2200-840 560X20-LV

PrevaLED Linear G5 | Linear Light Engines



### Product family features

- Module efficacy: up to 193 lm/W
- Available with luminous flux: 275 lm on 70 mm
- Available with luminous flux: 1,100 lm or 2,000 lm on 280 mm
- Available with luminous flux: 2,000 lm, 4,000 lm on 560 mm
- Available with luminous flux: 4,400 lm on 1,120 mm
- Available with luminous flux: 5,500 lm on 1,400 mm
- Available with color temperature: 3,000 K, 4,000 K or 6,500 K
- High initial color consistency:  $\leq 3$  SDCM
- Average lifetime (L80 B50):  $> 70,000$  h (temperature at  $T_c = 50$  °C)
- CE marked, ENEC certified; UL listed

### Product family benefits

- Slim luminaire design by small and flexible form factor
- High homogeneity thanks to small LED pitch
- High voltage (HV) for serial connection
- Low voltage (LV) for parallel connection
- High voltage (HV) optimized for non-isolated, low voltage (LV) optimized for SELV operation
- Adjustable luminous flux, efficacy and lifetime
- Direct the light where it's needed while using PrevaLED Linear Optics

### Areas of application

- Office
- Industry



## Product datasheet

### Technical data

#### Electrical data

Nominal voltage	23.5 V
Nominal current	0.5 A
Type of current	DC
On-mode power	12.2 W
Energy consumption in on-mode	12.2 kWh/1000h

#### Photometrical data

Luminous efficacy	184 lm/W
Color rendering index Ra	>80
Correlated color temperature CCT	4000 K
Colour consistency (McAdam ellipses)	3
Useful luminous flux ( $\Phi_{use}$ )	2168 lm


#### Light technical data

Starting time	< 0.1 s
Warm-up time (60 %)	< 2.00 s

#### LED module information

Number of LEDs per module	72
---------------------------	----

#### Dimensions & weight



Product weight	40.00 g
Height	5 mm
Length	560 mm
Width	20 mm

### Temperatures & operating conditions

Performance temp. acc. to IEC 62717	50 °C
Temperature range in operation at Tc point	-20...75 °C
Maximum temperature at tc test point	75 °C
Temperature range at storage	-30...85 °C
Ambient temperature range	-20...+75 °C

### Lifespan

Number of switching cycles	100000
Lumen maintenance factor LMF	96
L70B50 lifetime	100000 h

### Additional product data

Lighting technology used	LED
Predecessor EAN	4052899989498

### Certificates & standards

Standards	CE/ENEC/VDE
Type of protection	IP20
Energy efficiency class	C


### Logistical data

Commodity code	854141000000
----------------	--------------


### Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4052899607194
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

## Product datasheet








484525\_5 Year Osram Guarante  
(GB)



PL LIN G5 G6 Mounting Guidance 251021

### Download Data

File	
	Certificates PL ENEC 40031612 250920
	Declarations of conformity PL LIN Z5 CE 3812250 200820
	Declarations of conformity EU Declaration of conformity PL-LIN-Z4 family
	Declarations of conformity Declaraton of conformity PL-LIN-Z4
	CAD data 3-dim PL LIN Z5 Z6 2200 560x20 LV CADPDF 240220

## Product datasheet

---

### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899607194	PL-LIN-Z5 2200-840 560X20-LV	Shipping carton box 60	592 mm x 252 mm x 100 mm	14.92 dm <sup>3</sup>	2838.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.