

PL-LIN-Z5 2200-865 560X20-LV

PrevaLED Linear G5 | Linear Light Engines



Areas of application

- Office
- Industry

Product family benefits

- Slim luminaire design by small and flexible form factor
- High homogeneity thanks to small LED pitch
- High voltage (HV) for serial connection
- Low voltage (LV) for parallel connection
- High voltage (HV) for non-isolated, low voltage (LV) for SELV operation
- Adjustable luminous flux, efficacy and lifetime
- Direct the light where it's needed while using PrevaLED Linear Optics



Product datasheet

Product family features

- Module efficacy: up to 193 lm/W
- Available with luminous flux: 275 lm on 70 mm
- Available with luminous flux: 1,100 lm or 2,000 lm on 280 mm
- Available with luminous flux: 2,000 lm, 4,000 lm on 560 mm
- Available with luminous flux: 4,400 lm on 1,120 mm
- Available with luminous flux: 5,500 lm on 1,400 mm
- Available with color temperature: 3,000 K, 4,000 K or 6,500 K
- High initial color consistency: ≤ 3 SDCM
- Average lifetime (L80 B50): $> 70,000$ h (temperature at $T_c = 50$ °C)
- CE marked, ENEC certified; UL listed

Technical data

Electrical data

Nominal voltage	23.5 V
Nominal current	0.5 A
Nominal wattage	11.80 W
Rated wattage	11.80 W
Type of current	DC

Photometrical data

Light color LED	White
Luminous efficacy	184 lm/W
Standard deviation of color matching	≤3 sdcn
Color temperature	6500 K
Color rendering index Ra	>80
Rated peak intensity	690 cd
Nom. useful luminous flux 120°	2200 lm
Rated useful luminous flux 120°	2168 lm
Total useful luminous flux	2168 lm


Light technical data

Beam angle	120 °
Starting time	< 0.1 s
Warm-up time (60 %)	< 2.00 s
Rated beam angle (half peak value)	120.00 °

LED module information

Number of LEDs per module	48
---------------------------	----

Dimensions & weight



Product weight	40.00 g
Length	560.0 mm
Width	20.0 mm
Height	5.0 mm

Temperatures & operating conditions

Performance temp. acc. to IEC 62717	50 °C
Temperature range in operation at Tc point	-20...75 °C
Maximum temperature at tc test point	75 °C
Temperature range at storage	-30...85 °C
Ambient temperature range	-20...+75 °C

Lifespan

Number of switching cycles	100000
Rated lamp life time	50000 h
Lumen main.fact.at end of nom.life time	0.80
Nominal lamp life time	50000 h

Capabilities

Dimmable	Yes
-----------------	-----

Certificates & standards

Energy consumption	12 kWh/1000h
Energy efficiency class	A++
Standards	CE/ENEC/VDE
Type of protection	IP20

Product datasheet







Logistical data

Commodity code	854140100000
----------------	--------------



Guarantee

Download Data

File	
	Product Datasheet PL LIN G5 DS 190220 (EN)
	Certificates PL BA ENEC 40031612 161219
	Declarations of conformity PL LIN Z5 CE 3812352 290719
	Declarations of conformity EU Declaration of conformity PL-LIN-Z4 family
	Declarations of conformity Declaraton of conformity PL-LIN-Z4
	CAD data 3-dim PL LIN Z5 Z6 2200 560x20 LV CADPDF 240220

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899607200	PL-LIN-Z5 2200-865 560X20-LV	Shipping carton box 120	588 mm x 380 mm x 125 mm	27.93 dm ³	5347.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.