

Lok-it! HSD 300 W/80/P28

Lok-it! HSD | Short Arc Metal Halide lamps



Areas of application

- Entertainment
- Architainment



Product datasheet

Technical data


Electrical data

Nominal wattage	30000 W
Nominal voltage	950 V
Lamp voltage	95 V
Lamp current	32 A

Photometrical data

Nominal luminous flux	20500 lm
Color temperature	8700 K

Dimensions & weight



Diameter	2300 mm
Length	1223 mm
Light center length (LCL)	67.0 mm

Lifespan

Lifespan	2000 h
----------	--------

Capabilities

Burning position	Other
------------------	-------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	05-03-2024
Primary Article Identifier	4008321493989 4008321644831
Candidate List Substance 1	No declarable substances contained

Product datasheet

Declaration No. in SCIP database	No declarable substances contained
----------------------------------	------------------------------------

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure during operation, Lok-it! lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Appropriate filters must ensure that UV radiation is reduced to an acceptable level. Mercury is released if the lamp breaks. Special safety precautions must be taken. Information on safety and handling is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321644831	Lok-it! HSD 300 W/80/P28	Shipping carton box 1	57 mm x 57 mm x 173 mm	0.56 dm ³	172.00 g
4008321644848	Lok-it! HSD 300 W/80/P28	Shipping carton box 10	295 mm x 125 mm x 190 mm	7.01 dm ³	1824.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.