

## GinoLED HO Module G2

LED modules for street lighting



### Product family features

- Available with beam angle: 60°×60° and 90°×90°
- Available with color temperature: 4,000 K, 6,500 K
- Color rendering index  $R_a$ : 80
- Impact resistance: IK08
- Type of protection: IP65
- Lifetime (L70/B50): 50,000 h
- Operating temperature range: -30...45 °C
- Certificates: CE, CB, CQC
- Lifetime (L70/B50) for GL-HO 80: 50,000 h (temperature at  $T_p = 50$  °C)
- Lifetime (L70/B50) for GL-HO 120: 50,000 h (temperature at  $T_p = 55$  °C)
- Lifetime (L70/B50) for GL-HO 150/180: 50,000 h (temperature at  $T_p = 60$  °C)

### Product family benefits

- High module efficacy: up to 165 lm/W
- Integrated heat sink for optimal thermal management and tailored optical design
- Light weight design for easy installation

### Areas of application

- Airports, stations and factories
- Indoor courts, exhibition halls, warehouses

## Product family datasheet

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Sales and Technical Support

Sales and Technical Support [www.osram.com](http://www.osram.com)

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.