

GinoLED HO Module ECO

LED modules for street lighting



Product family features

- Available with beam angle: 60°×60° and 90°×90°
- Available with color temperature: 4,000 K, 6,500 K
- Color rendering index R_a : 80
- Impact resistance: IK08
- Type of protection: IP65
- Lifetime (L70/B50): 50,000 h
- Operating temperature range: -30...45 °C
- Certificates: CE, CB, CQC
- Lifetime (L70/B50) for GL-HO 80: 50,000 h (temperature at $T_p = 50$ °C)
- Lifetime (L70/B50) for GL-HO 120: 50,000 h (temperature at $T_p = 55$ °C)
- Lifetime (L70/B50) for GL-HO 150/180: 50,000 h (temperature at $T_p = 60$ °C)

Product family benefits

- High module efficacy: up to 146 lm/W
- Integrated heat sink for optimal thermal management and tailored optical design
- Light weight design for easy installation

Areas of application

- Airports, stations and factories
- Indoor courts, exhibition halls, warehouses

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Sales and Technical Support

Sales and Technical Support www.osram.com

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.