

# LEDDriving FL PSX24W



### Cool White color temperature of 6,000 K

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



### Superior brightness

More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



### Ultra compact LED replacement for conventional PSX24W fog lamps as socket solution

Easy installation with optimized compatibility

### New OSRAM LED fog lamps to increase safety and performance

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps with state-of-the-art LED technology. The color temperature of 6,000K provides for a stylish cool white look and improved visibility.



## Product family datasheet

### Technical data

Product description	Product information		General Product Information	Electrical Data	
	Product type (off-road vs. on-road)	Application (Category and Product specific)	Global order reference	Test voltage	Nominal wattage
LEDiving FL $\triangleq$ PSX24W	Off-road $\triangleq$ PSX24W	Mainly used for headlight/ fog light applications	2604CW	13.2 V	6 W

Product description	Nominal voltage	Photometric Data		Physical Attributes & Dimensions	Lifetime Data
		Nominal luminous flux	Luminous flux tolerance	Diameter	Lifespan Tc
LEDiving FL $\triangleq$ PSX24W	12.0 V	730 lm	$\pm 20$ %	18.0 mm	5000 hr

Product description	Lifespan B3	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
		Technology	Primary article identifier	Declaration no. in SCIP database
LEDiving FL $\triangleq$ PSX24W	2500 hr	LED	4062172058346   4062172058360   4062172401852	In work

## Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information. LEDriving CANBUS CONTROL UNIT (LEDCBCTRL102) avoids error messages on the board computer when using LED fog lights within 21 W applications. Refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee) for precise conditions.

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

