

Lightbar FX250-CB

Higher luminosity for improved safety on the road



Combo Beam
Combined beam of light



Lighting distance up to 320 meters
Improved far and near field illumination



Beam angle 5°
Exceptionally focused beam angle

Product datasheet



Increased brightness thanks to LED auxiliary lights for far and near field illumination

Particularly when driving on rural and dirt roads, a greater range of visibility can play a key role in ensuring safety. The LEDriving Lightbar FX250-CB is an ECE-compliant LED auxiliary light that provides additional, far field illumination on dark roads. Even in poor visibility conditions or at dusk, the ten high-performance LEDs reach a light distance of up to 320 meters and daytime lighting conditions with a color temperature of 6000 Kelvin. The auxiliary automotive light can be used as both a supplementary LED high beam headlight and a powerful working light. The light is fully ECE-compliant in both versions and therefore suitable for use on roads. An intelligent reflector design diverts the light from the LEDs so that oncoming traffic is only indirectly exposed to the light. With a beam angle of five degrees, oncoming vehicles are not needlessly blinded and the light is evenly distributed. Robust and durable thanks to superior craftsmanship. As an LED auxiliary light, the LEDriving Lightbar FX250-CB has to withstand quite a bit. Its compact housing and extremely robust polycarbonate lens can do just that. The LED bar for automobiles can stand up to the most extreme weather and environmental conditions. What's more, the integrated driver and thermal management system ensure that the ten high-performance LEDs will not overheat. Complete polarity protection both prevents damage from excess voltage and contributes to a longer lifespan for the LED bar. Safe and flexible both on-road and off-road. Its variability gives the LEDriving Lightbar FX250-CB a flexible range of uses. The LED lights can be installed on cars, utility vehicles, recreational and 4x4 vehicles and agricultural vehicles. Thanks to their extreme luminosity, they are also ideal as LED working lights on off-road vehicles. The powerful 2700 lumen LED auxiliary light provides the highest optical efficiency for every application and an aesthetic, homogeneous light distribution.

Product datasheet

Technical data

Product information

Application (Category and Product specific)	Additional high beam application
---	----------------------------------

General Product Information

Global order reference	LEDDL103-CB
------------------------	-------------

Electrical Data

Nominal wattage	35.00 W
Test voltage	13.5 V

Photometric Data

Nominal luminous flux	2700 lm
Light distance at 1lx	320 m

Physical Attributes & Dimensions

Product weight	1200.00 g
----------------	-----------

Lifetime Data

Lifespan Tc	5000 hr
Guarantee	5 years

Additional product data

Connector to lamp	DT Connector
-------------------	--------------

Capabilities

Technology	LED
------------	-----

Certificates & standards

Approval marks – approval	E4 approval
Type of protection	IP67
Standards	ECE R10, R112

Logistical data

Commodity code	85122000900
----------------	-------------

Environmental & Regulatory Information

Product datasheet










Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	05-09-2024
Primary article identifier	4052899595354
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	1efd6f45-d91e-402d-8d98-01f73e6f1f81

Logistical Data




Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899595354	Lightbar FX250-CB	Folding carton box 1	388 mm x 90 mm x 137 mm	4.78 dm ³	1398.00 g
4052899595361	Lightbar FX250-CB	Shipping carton box 4	408 mm x 295 mm x 208 mm	25.03 dm ³	6044.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 User instruction LEDriving
 Movie application LEDriving D and W Image Video Bringing light to life (EN)
 Movie application Working and Driving Lights Amarak Winter
 Movie application LEDriving Driving and Working Lights Reference Video (EN)
 Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
 Movie application LEDriving driving & working lights in application (EN)
 Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
 Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
 Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance

Product datasheet

	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads
	ref_pim_amsproduct360degreeimages LEDriving LIGHTBAR FX250-CB, LEDriving LIGHTBAR FX250-SP

Legal advice

In vehicles with 12/24 volts, auxiliary lights must be installed in pairs
Precise terms and conditions at:
www.osram.com/guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



OSRAM