

# Lightbar FX500-CB SM

Higher luminosity guarantees improved safety on the road



### Central and individual installation

Individual installation is possible thanks to twofold ECE certification



### Lighting distance up to 440 meters

Improved far and near field illumination



### Combo Beam

Combined beam of light



### LED auxiliary lights enhance driving pleasure

Improved far field illumination on dark rural and dirt roads – it's no problem for the LEDriving Lightbar FX500-CB. Its 20 intense, high-performance LEDs give the LED high beam a light distance up to 440 meters and ensure improved road safety for drivers. Even at dusk or in compromised lighting conditions, the LED bars for automobiles provide daylight conditions at a strong 6000 Kelvin without needlessly blinding oncoming traffic. The intelligent reflector design diverts the light from the LEDs so that oncoming traffic is only indirectly exposed to the light. The light is evenly distributed at a five degree angle. Robust, durable and versatile. Whether used as a LED working light or as an auxiliary high beam for the car – the powerful performance and long life of the LEDriving Lightbar FX500-CB make it a compelling choice. Equipped for a wide range of uses, it defies environmental factors and is particularly robust thanks to the quality craftsmanship of its materials and hard-wearing polycarbonate lens. The integrated driver and thermal management system regulates the temperature of the LED automotive headlight and prevents damage caused by overheating. Full polarity protection ensures the LEDs are automatically shut off in the event of excess voltage. Brightness for a wide range of uses. The LEDriving Lightbar FX500-CB is pure pleasure both on and off-road. The ECE-compliant LED auxiliary light ensures better visibility and thus improved safety on roads. In addition, it adds a smart touch that enhances the off-road style of the vehicle. The LED headlight can be mounted on 12V vehicles as well as agricultural machines, utility vehicles, recreational, off-road and 4x4 vehicles. The power package with an intense 5500 lumen brightness scores with the highest optical efficiency and homogeneous light distribution with reduced glare.

## Product datasheet

### Technical data

#### Product information

Order reference	LEDDL104-CB SM
-----------------	----------------

#### Electrical data

Nominal wattage	70.00 W
-----------------	---------

#### Dimensions & weight

Product weight	2100.00 g
Length	0.0 mm

#### Country specific categorizations

Order reference	LEDDL104-CB SM
-----------------	----------------

#### Logistical data



Commodity code	851220009000
----------------	--------------

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899614079	LEDiving FX	Folding carton box 1	638 mm x 137 mm x 90 mm	7.87 dm <sup>3</sup>	2398.60 g
4052899614086	LEDiving FX	Shipping carton box 4	655 mm x 295 mm x 208 mm	40.19 dm <sup>3</sup>	10240.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 User instruction LEDiving
 Movie application LEDiving driving & working lights in application (EN)

#### Legal advice

Single mounting – installation in pairs is not necessary, two certified light sources

Precise terms and conditions at: [www.osram.com/guarantee](http://www.osram.com/guarantee)

## Product datasheet

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.