

BA-L-CX-840 G4

BackLED L CX G4 | LED modules for light advertising and backlighting



Product family features

- Color consistency in 3 SDCM
- Diffusive Optics technology
- Wide CCT options available
- IP66 Rated

Product family benefits

- High module flux output up to 160 lm
- Energy saving with high efficacy
- Wide beam angle for high uniformity
- Good solution to reduce system cost

Areas of application

- Backlighting



Technical data

Electrical data

Nominal voltage	12.0 V
Nominal wattage per chain	30.00 W
Nominal wattage per LED module	1.5 W
Accidental reverse input voltage protection up to	13 V
Input voltage range	12...13 V
Type of current	DC

Photometrical data

Color temperature	4000 K
Color rendering index Ra	80
Light color (designation)	Neutral White
Light color LED	Neutral white
Luminous flux per module chain	3240 lm
Luminous flux per LED module	162 lm
Luminous efficacy	108 lm/W
Standard deviation of color matching	≤3 sdcM
Luminous flux per LED module at Ta 25 °C	162 lm
Luminous flux per chain at Ta 25 °C	3240 lm



Light technical data

Beam angle	160 °
------------	-------

LED module information

Number of LEDs per module	3
Number of LED modules per chain	20
Minimum operable number of LED modules	1

Dimensions & weight



Length	4000 mm
Width	15.2 mm
Height	6.68 mm
Product weight	240.00 g
Module length	70.5 mm
Module pitch	200 mm

Temperatures & operating conditions

Temperature range in operation at T_c point	-25...75 °C ¹⁾
Temperature range at storage	-25...85 °C

¹⁾ At the T_c point

Lifespan

Lifespan	30000 h ¹⁾
-----------------	-----------------------

¹⁾ L70/B50 at T_c 75 °C

Additional product data

ID of contained light source	LS_SHZ_600384
-------------------------------------	---------------

Capabilities

Dimmable	Yes
Dimming range	1...100 %

Certificates & standards

Energy consumption	30 kWh/1000h
Type of protection	IP66



Product datasheet

Standards	Acc. to IEC 62471/Acc. to IEC 60598-1/Acc. to EN 60529/Acc. to EN 62031/Acc. to EN 61547/Acc. to EN 55015/CE
Approval marks – approval	BIS / CE
Energy efficiency class of the contained light source	F

Logistical data

Commodity code	940540399000
-----------------------	--------------

Download Data

File
 User instruction BackLED L CX G4 User Instruction
 Declarations of conformity CE BA-MINI-S&M-CP-8xx-G4 BA-L-CX-8xx-G4

Ecodesign regulation information:

ul>This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.

In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.

Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172145619	BA-L-CX-840 G4	Shipping carton box 30	350 mm x 250 mm x 230 mm	20.13 dm ³	8000.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product datasheet

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.