


LEDDriving SL C5W 6418 WHITE

Ideal replacement for any vehicle




Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional C5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for C5W

LEDDriving SL C5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional C5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

Product description	Electrical Data				Photometric Data
	Power input	Nominal voltage	Nominal wattage	Test voltage	Nominal luminous flux
LEDiving SL $\triangleq$ C5W	0.8 W	12 V	0 W	13.5 V	45 lm

Product description	Luminous flux tolerance	Physical Attributes & Dimensions	Lifetime Data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)
		Diameter	Lifespan B3	Lifespan Tc	Primary article identifier
LEDiving SL $\triangleq$ C5W	$\pm 30\%$	11.0 mm	2500 hr	5000 hr	4062172054126 4062172150651 4062172054140 4062172401159

Product description	Candidate list substance 1	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDiving SL $\triangleq$ C5W	Lead	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	95682f27-d6b7-4151-ab69-cba0f44a2086 4f83cbb3-5bb8-46d9-b0d0-90cb2627a962 6697cab8-36c6-4db3-8425-09dae59efdc 10e60bb5-8b39-4d1f-8551-c46ae9a84cdd a95423f8-e9f7-4f9b-91d7-326600bc64dc 8bacbba0-9b26-4b24-82cf-75519f9f5e26 122507a5-f401-4168-bc67-e2333e8a1a33 89d2ab14-22f4-42c2-afca-16d0b8a637b8 4e91a51d-54e6-41cd-aa04-c08cac7661e6 8021f719-e7de-457e-97c8-27fd6614ff14

Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.