

LEDDriving SL P21/5W YELLOW

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Amber



Replaces conventional P21/5W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21/5W

LEDDriving SL P21/5W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P21/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

Product type (off-road vs. on-road)	Off-road $\hat{=}$ P21/5W
Application (Category and Product specific)	Mainly used for signal/ indicator applications

General Product Information

Global order reference	7528DYP
------------------------	---------

Electrical Data

Power input	1.49 / 0.92 W
Nominal voltage	12.0 V
Nominal wattage	1 W
Test voltage	13.5 V
Power input tolerance	\pm 25 %

Photometric Data

Nominal luminous flux	55/10 lm
Luminous flux tolerance	\pm 25 %
Light color LED	Yellow

Physical Attributes & Dimensions

Diameter	27.0 mm
Product weight	16.00 g
Length	52.5 mm
Lamp base	BAY15d

Lifetime Data

Lifespan B3	1500 hr
Lifespan Tc	4000 hr
Guarantee	4 years

Capabilities

Technology	LED ¹⁾
------------	-------------------

¹⁾ Light-emitting diode lamp

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	06-09-2024

Product datasheet


Primary article identifier	4062172151702 4062172401333
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	14f3180f-982a-4665-b20f-9dc2ee4f8284

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172151702	LEDriving SL \triangleq P21/5W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm ³	44.00 g
4062172151719	LEDriving SL \triangleq P21/5W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm ³	256.00 g
4062172401333	LEDriving SL \triangleq P21/5W	Blister 2	95 mm x 27 mm x 135 mm	0.35 dm ³	43.00 g
4062172401340	LEDriving SL \triangleq P21/5W	Shipping carton box 10	142 mm x 104 mm x 104 mm	1.54 dm ³	250.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File
 Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Canbus compatible Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

