

LEDDriving SL P21W WHITE

Ideal replacement for any vehicle




Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P21W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21W

LEDDriving SL P21W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

| | |
|---|--|
| Product type (off-road vs. on-road) | Off-road $\hat{=}$ P21W |
| Application (Category and Product specific) | Mainly used for signal/ indicator applications |

General Product Information

| | |
|------------------------|---------|
| Global order reference | 7506DWP |
|------------------------|---------|

Electrical Data

| | |
|-----------------------|------------|
| Power input | 1.8 W |
| Nominal voltage | 12.0 V |
| Nominal wattage | 1 W |
| Test voltage | 13.5 V |
| Power input tolerance | \pm 25 % |

Photometric Data

| | |
|-------------------------|------------|
| Nominal luminous flux | 160 lm |
| Luminous flux tolerance | \pm 25 % |
| Color temperature | 6000 K |
| Light color LED | Cool white |

Physical Attributes & Dimensions

| | |
|----------------|---------|
| Diameter | 25.0 mm |
| Product weight | 16.00 g |
| Length | 52.5 mm |
| Lamp base | BA15s |

Lifetime Data

| | |
|-------------|---------|
| Lifespan B3 | 1500 hr |
| Lifespan Tc | 4000 hr |
| Guarantee | 4 years |

Capabilities

| | |
|------------|-------------------|
| Technology | LED ¹⁾ |
|------------|-------------------|

¹⁾ Light-emitting diode lamp

Environmental & Regulatory Information

| |
|--|
| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |
|--|

Product datasheet


| | |
|----------------------------------|--|
| Date of declaration | 09-07-2024 |
| Primary article identifier | 4062172348652 4062172152181 4062172401210 |
| Candidate list substance 1 | Lead |
| CAS No. of substance 1 | 7439-92-1 |
| Safe use instruction | The identification of the Candidate List substance is sufficient to allow safe use of the article. |
| Declaration no. in SCIP database | e75f732e-151e-4392-9807-f15711d460b4 |

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|--------------------------------|------------------------------|--------------------------------------|----------------------|--------------|
| 4062172152198 | LEDriving SL \triangleq P21W | | - x - x - | 1.96 dm ³ | |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File |
|---|
|  Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatible Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM