# **OSRAM**

# LEDriving SL W21W/5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White

# Replaces conventional W21W5W lamps

Easy upgrade to LED technology with plug & play solutions



# Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for W21/5W

LEDriving SL W21W/5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional W21W/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# Product datasheet

# Technical data

# **Product information**

Order reference	7515DWP	
Product type (off-road vs. on-road)	Off-road ≙ W21/5W	
Application (Category and Product specific)	Mainly used for signal/ indicator applications	


# **Electrical data**

Power input	2.7 W
Nominal voltage	12.0 V
Nominal wattage	1.90/0.40 W
Test voltage	13.5 V
Power input tolerance	±10 %

#### Photometrical data

Luminous flux	155/25 lm	
Luminous flux tolerance	±25 %	
Color temperature	6000 K	
Light color LED	Cool white	

# **Dimensions & weight**



Diameter	20.0 mm
Product weight	12.00 g
Length	47.5 mm

# Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

# Product datasheet

#### Additional product data

Base (standard designation)	W3x16q
-----------------------------	--------

# **Capabilities**

 $<sup>^{1)}</sup>$  Light-emitting diode lamp

# **Country specific categorizations**

#### **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	07-03-2024		
Primary Article Identifier	4062172152266   4062172401494		
Candidate List Substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration No. in SCIP database	4746391f-7cf0-4291-a57a-5bc608210a87		

# Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172152266	LEDriving SL ≙ W21/5W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm <sup>3</sup>	36.00 g
4062172152273	LEDriving SL ≙ W21/5W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm <sup>3</sup>	215.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Download Data

File



Brochures

LEDriving Retrofits - Exchange overview (EN)

# Safety advice

# Product datasheet

#### Canbus compatible

Coloured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

