# LEDriving SL W21W RED

## Ideal replacement for any vehicle



Suitable for various vehicle exterior applications Available in Red


#### **Replaces conventional W21W lamps**

Easy upgrade to LED technology with plug & play solutions



OSRAM

Reliable OSRAM quality stands for less lamp replacements 4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



#### Suitable LED replacement for W21W

LEDriving SL W21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional W21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

## Technical data

## **Product information**

Order reference	7505DRP	
Product type (off-road vs. on-road)	Off-road = W21W	
Application (Category and Product specific)	Mainly used for signal/ indicator applications	


## **Electrical data**

Power input	2 W
Nominal voltage	12.0 V
Nominal wattage	1.40 W
Test voltage	13.5 V
Power input tolerance	±10 %

## Photometrical data

Luminous flux	60 lm
Luminous flux tolerance	±25 %
Light color LED	Red

# Dimensions & weight



Diameter	20.0 mm
Product weight	11.30 g
Length	47.5 mm

## Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

## Additional product data

Base (standard designation)	W3x16d	
Capabilities		
Technology	LED <sup>1)</sup>	
<sup>1)</sup> Light-emitting diode lamp		
Country specific categorizations		
Order reference	7505DRP	

## **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	09-02-2024
Primary Article Identifier	4062172149259   4062172401616
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	f3620d80-08fb-43ae-b294-cdeaeb59531d

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172149259	LEDriving SL ≙ W21W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm <sup>3</sup>	35.00 g
4062172149266	LEDriving SL ≙ W21W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm³	208.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
Brochures LEDriving Retrofits - Exchange overview (EN)

## Safety advice

## Canbus compatible

Coloured lamps for usage behind coloured glass

#### Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

