

LEDDriving SL P21/5W WHITE

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Cool White



Replaces conventional P215W lamps

Easy upgrade to LED technology with plug & play solutions

Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for P21/5W

LEDDriving SL P21/5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product family datasheet

Technical data

| Product description | Product information | | | Electrical data | | |
|-----------------------------------|---------------------|-------------------------------------|--|-----------------|-----------------|-----------------|
| | Order reference | Product type (off-road vs. on-road) | Application (Category and Product specific) | Power input | Nominal voltage | Nominal wattage |
| LEDDriving SL \triangleq P21/5W | 7528DWP | Off-road \triangleq P21/5W | Mainly used for signal/ indicator applications | 2.50 / 0.5 W | 12.0 V | 2.00/0.40 W |

| Product description | Power input tolerance | Test voltage | Photometrical data | Dimensions & weight | | Lifespan | |
|-----------------------------------|-----------------------|--------------|--------------------|---------------------|----------|-------------|-------------|
| | | | Luminous flux | Length | Diameter | Lifespan B3 | Lifespan Tc |
| LEDDriving SL \triangleq P21/5W | $\pm 25\%$ | 13.5 V | 145/30 lm | 52.5 mm | 27.0 mm | 1500 h | 4000 h |

| Product description | Additional product data | Capabilities | Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) | |
|-----------------------------------|-----------------------------|-------------------|--|-------------------------------|
| | Base (standard designation) | Technology | Date of Declaration | Primary Article Identifier |
| LEDDriving SL \triangleq P21/5W | BAY15d | LED ¹⁾ | 09-02-2024 | 4062172151726 4062172401197 |

| Product description | Candidate List Substance 1 | CAS No. of substance 1 | Safe Use Instruction | Declaration No. in SCIP database |
|-----------------------------------|----------------------------|------------------------|--|--------------------------------------|
| LEDDriving SL \triangleq P21/5W | Lead | 7439-92-1 | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 026eb835-3aa5-4bfa-a635-bb4b42c468ab |

¹⁾ Light-emitting diode lamp

Download Data

| File | |
|---|---|
|  | Brochures LEDriving Retrofits - Exchange overview (EN) |

Safety advice

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.